

# Armored Toyota Land Cruiser 200

The Toyota Land Cruiser is the most popular armored off-road vehicle worldwide with the best dealer network. It is also available in a luxury version based on the Lexus LX570. The armored Land Cruiser 200 or Lexus LX570 comes complete with reinforced suspension and brakes which make the road performance of this vehicle very comfortable. Protection levels can vary from handgun to armor piercing and blast depending on customer requirements. This protection includes four doors, all glass, front, center, and rear pillars, roof, firewall, front and rear headers, and tailgate. The floor is protected against two DM51 grenades or two M67 grenades, detonated simultaneously. The body, frame, axles, brakes, suspension, and door hinges are reinforced or replaced in order to maintain the original driving characteristics and reliability of the vehicle.

## KEY FEATURES

---

Fully customizable per customer requirements

---

Blends in around the globe

---

Armor up to armor piercing protection



# Armored Toyota Land Cruiser 200

## BASIC PACKAGE

- Multi-layered ballistic glass
- Run-flat tire insert system
- Protected floor
- Battery protection

## OPTIONAL FEATURES

- Protected fuel tank
- Intercom
- Siren/PA System
- Fire suppression system
- Tinted windows
- Emergency flashing lights
- Ram bumpers
- Tactical interior package
- Additional options available

## CONFIGURATION OPTIONS

- Left-hand or right-hand drive
- Manual or automatic transmission
- Gasoline or diesel engine

## VEHICLE SPECIFICATIONS

Base unit:	Toyota Land Cruiser 200
Engine:	5.7L V8 EFI DOHC Gasoline
Transmission:	Automatic
Max. Power:	381 hp (125 kW) @ 5600 rpm
Max. Torque:	401 lb-ft (543 Nm) @ 3600 rpm
Length:	194.9 in (4,950 mm)
Height:	74 in (1,880 mm)
Width:	77.6 in (1,971 mm)
Wheelbase:	112.2 in (2,850 mm)
Protection level:	B4 to B7
Steering version:	LHD or RHD



## VEHICLE SPECIFICATIONS

Base unit:	Toyota Land Cruiser 200
Engine:	3.0L Diesel
Transmission:	Manual/Automatic
Max. Power:	173 hp (127 kW) @ 3400 rpm
Max. Torque:	302 lb-ft (410 Nm) @ 1600-2800 rpm
Length:	194.9 in (4,950 mm)
Height:	74 in (1,880 mm)
Width:	77.6 in (1,971 mm)
Wheelbase:	112.2 in (2,850 mm)
Protection level:	B4 to B7
Steering version:	LHD or RHD



## FOR MORE INFORMATION CONTACT:

BAE Systems  
 9113 Le Saint Drive  
 Fairfield, OH 45014 USA  
 Telephone 513-881-9800  
 Toll Free 800-697-0307  
 Fax 513-881-4850  
 Email [ss.support@baesystems.com](mailto:ss.support@baesystems.com)  
[www.baesystems.com/sss](http://www.baesystems.com/sss)

This document gives only a general description of the product(s) or services and except where expressly provided otherwise shall not form part of any contract. From time to time, changes may be made in the products or the conditions of supply. BAE Systems reserves the right to change product specifications without prior notice.