

# Eclipse RF™ Products

## RXR6332



The **RXR6332** is a 3U VPX wideband dual-channel high-frequency direct-conversion receiver packaged in a rugged, conduction-cooled module. It is ideal for applications that require an open, standards-based solution to the reception of signals in the high-frequency spectrum.

The RXR6332 is a standard product offering in the R6000 series of signals intelligence (SIGINT) modules and integrated hardware subsystems. Eclipse has been delivering high-performance, open-standards based products to the SIGINT market for more than 25 years.

### Key features and benefits

- Two HF receiver channels per 3U VPX module are digitally tunable from 100 kHz to 110 MHz with sub-Hz resolution for precise tuning
- Excellent tuning speed and spectral purity enables the detection of short duration signals in the presence of noise
- RF pre-selection filters on each input channel provide optimal performance in the presence of adjacent interfering signals
- Optional pre-selection by-pass mode presents the entire spectrum up to 110 MHz to the analog-to-digital converter for wideband search mode
- Each HF input channel is sampled by a corresponding analog-to-digital converter at 250 MS/sec with 16-bit resolution for high-dynamic range
- 32 narrowband digital down converter filters per high-frequency input channel support simultaneous narrowband and wideband operation
- N-channel coherent operation employing one to many receivers enables spatial processing applications, such as direction finding and beamforming
- Modular open-architecture design complies with VITA-46, -48, -49, -67, and emerging upper-level standards, such as SOSA and CMOSS, which are VITA standards based
- Slot compatible with the Eclipse RXR6322 VHF/UHF receiver in mechanical, electrical, and software interfaces providing flexibility to the system integrator when optimizing solutions for a given mission

## RXR6332 specifications

### Radio frequency (RF)

Frequency range	100 kHz to 110 MHz
Tune resolution	Sub-Hz in re-sampler direct digital controls
Input impedance	50 Ohms
Voltage standing wave ratio	Less than 2.5:1
Pre-selection	14 pre-selection filters
Maximum input level	+24 dBm
Gain	30 dB typical
LO re-radiation	< -90 dBm
Noise figure	16 dB maximum, 14 dB typical, 13 dB typical at maximum gain
In band of final IF (IIP3)	+ 15 dBm at 15 dB gain, + 25 dBm at max attenuation
Out of band	+30 dBm typical at 0 dB attenuation, two tone
Second-order intercept	+ 50 dBm min, +60 dBm typical

### External reference

(Recommended minimum performance specifications)

Frequency	10 MHz +/- 5 PPM or better
Amplitude	0 dBm +/- 3 dB
Harmonics	-20 dBc maximum
Non-harmonic spurious	-80 dBc maximum
Source voltage standing wave ratio	1.5:1 max (50 Ohms)

### Digital specifications

Wideband data format	16-bit real or 16-bit I&Q complex
Filtered narrowband	16-bit I&Q complex
Output sample data rate	Set by selected re-sampler (80, 40, 12.8 cMsps) Consult factory for options
IF bandwidths number	500 Hz to 2 MHz (>2 MHz with reduction in of available DDCs)
Wideband gain control modes	Attenuation range 45 dB with 1 dB steps
Gain control	Fast attack, slow decay, freeze, dump attack-freeze, manual
Signal memods	AM, FM, USB, LSB, CW, OOK u/a-law TDM output, FFT options
Delay memory	250 Mbytes/channel

### Data and control interface

Control/status	PCIe or 1 Gig-E
Data plane	PCIe or 1 Gig-E
Sync input/output	Backplane daisy chain
Coherency	LO and timing distribution for coherent operation of multiple receivers (N channel)

### Size, weight and power

VPX voltages required (standard)	3.3, 5, 12, -12 VDC
Power dissipation	44 Watts typical, 55 Watts maximum
Temperature	Operational from -20 to +70 degrees Celsius at module rails
Humidity	95 percent non-condensing
Size	3U-160 VPX 1 inch pitch
Weight	27 ounces

### For more information contact:

BAE Systems  
John Brickman  
17111 Waterview Pkwy  
Dallas, Texas 75252  
**T:** 972 699 8580  
**E:** john.brickman@baesystems.us  
**W:** baesystems.com/Eclipse  
Cleared for open publication on 07/18

### Disclaimer and copyright

This document gives only a general description of the product(s) and service(s) and, except where expressly provided otherwise, shall not form any part of any contract. From time to time, changes may be made in the products or the conditions of supply.

BAE SYSTEMS is a registered trademark of BAE Systems plc.

©2025 BAE Systems. All rights reserved.

CS-18-C79\_RXR6332