

# NavFire™ GPS Receiver

Essential **accuracy**

## Trusted military GPS for weapons and artillery

In today's unpredictable battlespace, launching weapons safely and accurately is critical to mission success. NavFire™ is the smallest integrated military Global Positioning System (GPS) and anti-jamming system in the proven family of BAE Systems' gun-hardened receivers for weapons.

Leveraging over 45 years of military GPS experience and advanced technical expertise in anti-jamming and high-g microelectronics, BAE Systems provides you with a 40 mm 25,000 g-hardened GPS receiver for your military needs.

NavFire is a 24-channel, dual-frequency, all-in-view receiver capable either as a stand-alone system or integrated with an Inertial Navigation System (INS). Powered by state-of-the-art technology, NavFire provides enhanced direct-Y acquisition, built-in digital nulling for high-jamming immunity, and fast initial acquisition.



### Key features and benefits

- Military encrypted GPS for weapons
- <2 m position accuracy (typical with aiding)
- Small form factor (40 mm)
- Artillery/gun hardened up to 25,000 g-shock
- Single die SAASM with KDP (GPS directorate approved)
- 24 channels with all-in-view, dual-frequency (L1/L2) track, and navigation (software upgradeable to 48 channels)
- Fully integrated digital anti-jamming electronics with dual RF inputs (>86 dB J/S while tracking)
- Fast direct-Y code acquisition (<6 sec, nominal)
- High-speed serial interfaces
- Low-cost flexible applications (artillery/UAV)

## Small size, high accuracy

Small in size yet high in accuracy and reliability, the NavFire is a cost-effective system specifically designed to meet the mission needs of gun-hardened applications. The NavFire delivers precise GPS navigation either as a stand-alone system or when integrated with an INS.

## Precise

This integrated receiver offers full Precise Positioning Service (PPS) accuracy. Simultaneous L1/L2 operation provides real-time ionosphere corrections for further accuracy enhancements. Its primary communication interface is a high-speed LVCMOS serial port. The integrated anti-jamming solution utilizes two-element digital nulling for improved jamming immunity. Additionally, this system has an Ultra Tight Coupling (UTC) unit interface option that improves both anti-jamming performance and navigation accuracy.

## Growth path

Scalable RF design (one or two channels) and field-programmable software eases maintenance, provides a growth path, and reduces life-cycle cost for use in ever-changing jamming environments. Delivery is assured by using common critical components, processes, and manufacturing lines that deliver over 100,000 Selective Availability Anti-Spoofing (SAASM)-based GPS receivers per year.



# Delivers precise GPS navigation

## System characteristics

Receiver	L1 frequency, C/A and P or Y code* L2 frequency, P or Y code* SAASM architecture Field-reprogrammable software
Dynamics	>10 g acceleration Supports spinning applications
TTFF	<6 sec (conditions apply)
Time accuracy	< ±30 nanoseconds RMS
Position accuracy	<3 m CEP* <2 m typical with aiding* Up to 25 Hz PVT solution update rate 1 Hz pseudo range, delta range update rate
Velocity accuracy	<0.07 m/sec RMS typical
Crypto key	Serial port, SKL, CYZ-10

## Reliability


- Comprehensive built-in-test
- Supports data hold (up to 8 min)
- Field clock recalibration for extended storage
- Storage life >20 years

## Interfaces

- One or two RF antenna inputs (L1/L2)
- Primary power, auxiliary power
- Serial host control – LVCMOS (RS-232), up to 230 Kbaud
- Host controlled Ultra Tight Coupling (UTC)
- DS-101
- 1/10 PPS CPS or UTC
- Discretes for GPS programming
- KDP programming, key zeroization

## Physical characteristics

Power	<2.8 W
Weight	2.8 oz (80 g)
Size	1.64 D x 0.95 in. H (41.3 x 24.13 mm)
Temp range	-45°C to +85°C (operating) -54°C to +85°C (storage)
Shock	Up to 25,000 g



\* Export of Precise Positioning Service (PPS) units is authorized for GPS Memorandum of Understanding countries only. PPS security modules must be obtained through Foreign Military Sales (FMS) procurement.

## For more information contact:

BAE Systems

P. O. Box 868  
Nashua, New Hampshire 03061-0868

**W:** [baesystems.com/gps](http://baesystems.com/gps)

Cleared for open publication on 07/20  
Approved for public release: unlimited distribution.  
Not export controlled per ES-NSS-071420-0008

## Disclaimer and copyright

This document gives only a general description of the product(s) and service(s) and, except where expressly provided otherwise, shall not form any part of any contract. From time to time, changes may be made in the products or the conditions of supply.

BAE SYSTEMS is a registered trademark of BAE Systems plc.  
©2020 BAE Systems. All rights reserved.  
20-C96-08