

AN/APX-122A

MKXIIA and Mode S Interrogator



The **AN/APX-122A** is the IFF interrogator system for the next-generation carrier-based airborne early warning system.

BAE Systems, with decades of experience in IFF, has designed the AN/APX-122A based on a long legacy of IFF products. The design emphasizes performance, reliability, risk reduction, flexibility, and reduction of life-cycle costs. It places a high priority on standardization and commonality, with growth requirements carefully considered to ensure architecture that is compatible with future needs. The AN/APX-122A is well suited to provide IFF capabilities on a wide variety of platforms.

The E-2D Advanced Hawkeye aircraft is designed to concentrate battle management, theater-air-missile defense, and multiple sensor fusion capabilities into one platform. The AN/APX-122A system operates in conjunction with the new radar and secondary antenna collocated in the rotodome. In addition to mechanical scan capabilities, the system uses an electronically controlled beam forming network for E- scan sector operation. The system is suitable for all AEW, ASW, and SAR applications and can be integrated with a variety of radar systems on the host aircraft.

The AN/APX-122A incorporates state-of-the-art technology and is implemented using VME open system architecture to ensure flexibility and growth. Extensive use of microprocessors and FPGA technology allows configuration of system interfaces to a variety of platform applications.

The AN/APX-122A is capable of interrogating in modes 1, 2, 3/A, C, 4, 5 and S. Any or all of these modes may be enabled continuously or in the azimuthal sectors of choice and can interrogate two different modes on the same interpulse period. Embedded predictive tracker maintains a track database on all targets in the surveillance volume.

The system uses a dedicated fiber LAN interface with the mission computer and employs a dedicated fiber interface for video output data to operator displays.

Features and benefits

- Mark XIIA and Mode S interrogation and reply evaluation
- Modes 1,2,3/A,C,4, 5, S (Supermode)
- Monopulse reception processing
- ISLS and RSLs processing
- Includes beam former network with E-scan capability
- Operates in conjunction with next generation E-2D radar, mission computer, and displays
- Extensive BIT and loop test capability

Specifications

Dimensions and weight	CY-8913A/APX-122 CV-4415/APX-122	19.63" height x 23.81" width x 16.33" depth, 128.25 pounds 9.75" height x 16.50" width x 12.12" depth, 91.7 pounds
Certifications	AIMS 03-1000B certification	

For more information contact:

BAE Systems

Dhanraj Gobin
450 Pulaski Road, M/S GNY010171
Greenlawn, NY 11740

T: 631 262 8195

E: dhanraj.gobin@baesystems.com

W: baesystems.com/IFF

Cleared for open publication on **04/21**

Disclaimer and copyright

This document gives only a general description of the product(s) and service(s) and, except where expressly provided otherwise, shall not form any part of any contract. From time to time, changes may be made in the products or the conditions of supply.

BAE SYSTEMS is a registered trademark of BAE Systems plc.
©2020 BAE Systems. All rights reserved.
CS-20-A90-07