

AN/ARC-164A

remote and panel mount radios

Ultra high frequency (UHF) multi-band airborne communication systems

The panel mount and remote AN/ARC-164A radio are part of BAE Systems' new Starfire product line of high performance, software defined radios (SDR) with extensive design reserve capacity. Software upgradeable radio capabilities address obsolescence while providing a cost-effective path to future enhancements for the installed base of fixed and rotary wing platforms.

We pioneered HAVE QUICK, embedded, anti-jam, electronic counter-counter measures (ECCM), the predecessor of SATURN, which is the next generation of airborne radios. With more than 100,000 legacy systems fielded across 70 countries, our radios are positioned to provide enhanced communication capabilities for the most demanding environments. The Starfire product line supports new and third party control and flight management systems. These airborne radios can communicate cipher text on all frequencies and modes when used in conjunction with external encryption such as TSEC/KY-58 VINSON or KY/SY-100M. Battle-proven, these systems provide warfighters with a tactical advantage.



AN/ARC-164A
MXF-4059
remote mount

AN/ARC-164A
MXF-4068
panel mount

Features and benefits

- Automatic direction finding capability supports operations with external direction finding equipment.
- These SDRs support a broader range of waveforms and capabilities including potential for civil communications like APCO-25 and TETRA.
- Software programmability allows for a broad range of capability configurations with and without ECCM.
- Qualified to military standards, the radios meet domestic and international interoperable requirements for the U.S DoD, NATO services, and coalition airborne applications.

Physical characteristics

Nomenclature	Dimensions (inches)			Weight	Input power
	Height	Width	Depth	Max lbs.	Watts
MXF-4059 (Remote RT)	4.840	4.950	7.730	9.00	200**
MXF-4068 (Panel mount RT)	4.840	4.740	8.822*	9.00	200**
C-11718	4.875	5.750	5.440	4.32	20
MXF-243	2.980	5.740	5.450	3.00	20
MT-4838	1.325	6.750	5.490	1.26	N/A

*Depth measurement includes rear connector and front face of control knobs.
Measurement is 6.772 from DZUS panel to rear connector.

**150W option to support legacy platforms

Radio system items

Nomenclature	Part No.	Description
C-11718	707793-806	Remote control (28 V lighting)
C-11718	707793-807	Remote control (5 V lighting)
MXF-243	902197-817	Remote control (5 V lighting)
MXF-243	902197-818	Remote control (28 V lighting)
MT-4838	707177-801	Mount
MXF-4059	903148-801	Receiver/transmitter remote mount/HQ I/II/SATURN
MXF-4068	903148-801	Receiver/transmitter panel mount/HQ I/II/SATURN IPL RED Lighting
MXF-4068	903148-802	Receiver/transmitter panel mount/HQ I/II/SATURN IPL WHITE Lighting
MXF-4068	903148-806	Receiver/transmitter panel mount/HQ I/II/SATURN NVIS GREEN A Lighting

General characteristics

Frequency range	225 to 399.975 MHz (control dependent)
Channel spacing	5 kHz and 25 kHz 8.33 kHz (ED-23C) with expanded VHF frequency range
Frequency accuracy	< 1 ppm
Remote mount	MIL-STD-1553, RS-422
Presets	99 channels (expandable)

For more information contact:

BAE Systems
Multiband Communications and Crypto (MCC)
5001 US 30 West, Suite 400
Ft. Wayne, IN 46818

T: 1-877-227-2231

W: baesystems.com/starfireradios

Cleared for open publication on **07/20**

BAE Systems | AN/ARC-164A

Encryption

Internal (optional)	Commercial AES
External	Compatible with KY-58/M, KY-100/M, & SY-100

Transmitter

Power output

AM	10 W
FM	20 W

Modulation

AM	80%, 300-3,200 Hz
FM	5.6 kHz deviation, 300-3200 Hz
AM	80%; 16 kbps nonsecure/secure data

Modes of operation

AM	225 to 399.975 MHz
FM	225 to 399.975 MHz (control dependent)
Range	(max) 30MHz to 2 GHz (optional)
Plain voice	A3E or F3E
Ciphered voice	A1D or F1D
Data transmission	A1D or F1D
ECCM options	HAVE QUICK I/II, SATURN, RPW, SINCGARS (available only with expanded VHF frequency range)

Environmental

General test method	MIL-STD-810G MIL-E-5400 Class 1 (modified)
Temperature range	-40°C to 71°C operating
Altitude	55,000 ft
Random vibration	15 Hz to 2 kHz
Operational	11.5 g rms
Endurance	12.6 g rms
Other	Crash safety
Humidity	95%, 10 days
EMI/EMC	MIL-STD-461G
Primary power	MIL-STD-704A 22 VDC-29 VDC

Disclaimer and copyright

This document gives only a general description of the product(s) and service(s) and, except where expressly provided otherwise, shall not form any part of any contract. From time to time, changes may be made in the products or the conditions of supply.

BAE SYSTEMS is a registered trademark of BAE Systems plc.
©2020 BAE Systems. All rights reserved.

ES-C4ISR-072320-0147
CS-20-C11-02