


# RH1020B radiation-hardened FPGA




The RH1020B radiation-hardened field-programmable gate array is a fully guaranteed device targeted for use in military and space applications. It is fabricated using BAE Systems' rad-hard 0.8 $\mu$  epitaxial bulk complementary metal-oxide semiconductor process. The process architecture offers gate array flexibility, high performance, and fast design implementation through user programming.

While it takes six months from the date of design submission for a traditional application-specific integrated circuit to be produced and delivered, customers can modify their FPGA chip designs up to the day before we deliver them. BAE Systems has achieved full DoD Qualified Manufacturer List (QML) certification, assuring that quality management, procedures, processes, and controls are in place from wafer fabrication through final test. The RH1280B also belongs to this family of radiation-hardened FPGAs.

## BAE Systems' RH1020B with Actel designer software

Brings together silicon, synthesis, and simulation to create a complete and integrated design environment for designing BAE Systems' FPGAs.

- Integrated development environment including simulation, synthesis, and place-and-route tools for designs fewer than 50k gates
- Increased design simulation limit to 400k gates with unlimited synthesis, allowing designers to move up as their skills and density requirements increase
- Includes simulation up to 400k gates and place-and-route tools. Ideal for ASIC designers who are starting to use FPGAs in their designs, but have already invested in synthesis tools



## Key features

- 84-lead ceramic quad flatpack
- Significantly greater densities than discrete logic devices
- Design library with more than 500 macro functions
- Single-module sequential functions
- Wide-input combinatorial functions
- Up to two high-speed, low-skew clock networks
- Two in-circuit diagnostic probe pins support speed analysis to 50 MHz
- Non-volatile, user-programmable devices
- Unique in-system diagnostic and verification capability with silicon explorer
- Standard microcircuit drawing #5962R90965
- QML-compliant part
- Capacity
  - 3,000 system gates
  - 2,000 gate array equivalent gates
  - 6,000 PLD-equivalent gates
  - 50 TTL-equivalent packages
  - 20 20-pin PAL-equivalent packages
- Logic modules
  - 547 C-modules
- Flip-flops (maximum)
  - 273
- Routing resources
  - 22 horizontal tracks/channel
  - 13 vertical tracks/channel
  - 186,000 PLICE antifuse elements
- User I/Os (maximum)
  - 69
- Radiation levels
  - Total dose: 150 Krad (Si)
  - High-dose rate survivability
  - Latchup immunity guaranteed

### For more information contact:

BAE Systems  
9300 Wellington Road  
Manassas, Virginia 20110-4122

T: 571 364 7777

baesystems.com/rad750

Cleared for open publication on 06/08

### Disclaimer and copyright

BAE Systems reserves the right to restrict component sales based on application and volume. Please contact the factory for more information.

This document gives only a general description of the product(s) and service(s) and, except where expressly provided otherwise, shall not form any part of any contract. From time to time, changes may be made in the products or the conditions of supply.

BAE SYSTEMS is a registered trademark of BAE Systems plc.  
© 2025 BAE Systems. All rights reserved.  
CS-16-J26