



095871, Rev 21, May 15, 2025

Contracts Deliverable Requirements

Platforms & Services
Combat Mission Systems

baesystems.com



Formatted: Different first page header

ed: Font: 11 pt

ed: Font: 11 pt

ed: Font: 11 pt

ed: Footer, Left

BAE SYSTEMS

Contract Deliverable Requirements Manual

Platforms and Services Combat Mission Systems

095871, Rev 22

September 14, 2026



Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

REVISION HISTORY

Rev	Date	Change Description	Approved By	Change Request #
00	11/27/2012	New Document Release		BPMS-00647
01	09/03/2013	Added verbiage to CDR 017, deleted 071	Tom Frazho	BPMS-01446
02	09/20/2013	Added verbiage to 001, 032, changed verbiage to 057, 058, 059, 060, 061, 063, and 068	Tom Frazho	BPMS-01476
03	01/15/2014	Changes to CDR 006, 053 and 070	Tom Frazho	BPMS-01593
04	03/10/2015	Deleted the supplier Supplier website link	Tom Frazho	BPMS-02194
05	08/31/2015	Revisions to CDR 001, 002, 003, 004, 005, 006, 009, 016, 018, 019, 020, 023, 026, 028, 032, 034, 041, 042, 051, 057, 058, 059, 060, 081. Deleted 017, 040, 053, 054, 063, 068, 069, 070, 072, 073, 074, 075, 076, 077, 078, 079, 080. Added 083.; all reference of deleted CDRs have been removed from the body of the document; Consolidated all data submission CDRs into CDR 047; deleted 048, 049, 050, 051, 052	Tom Frazho	BPMS-02450
06	12/16/2015	Changes to CDR 034; Changes to CDR 006 for corrective action response to Louisville DCMA	Tom Frazho / Anthony Conley	BPMS-02612
07	01/14/2016	Re-instated CDR 017 back onto document	Tom Frazho / Anthony Conley	BPMS-02631
08	04/25/2016	Added new San Jose email address, changed any reference of Santa Clara to San Jose; added process approval to CDR 034	Tom Frazho / Anthony Conley	BPMS-02876
09	09/20/2016	Deleted CDR 002, 042, 047, 062, 081; "are located in the Supplier Quality Assurance Manual (SQAM)" added to CDR 001 as well as added verbiage in the 5 th and 8 th bullets below; verbiage added in CDR 003 and 004; in the 2 nd paragraph in 004 "the" was added and "Government" was deleted; CDR 005, 2 nd paragraph, verbiage was added and the 3 rd paragraph was added; last bullet added to CDR 007; deleted 4 th and 5 th bullets regarding training and approval prior to use for each individual part	Tom Frazho / Anthony Conley	BPMS-03124

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

		number; CDR 009 verbiage was added in the first bullet; CDR 010, "For each shipment" deleted, "(located in the SQAM)" added; "(located in the SQAM)" added to CDRs 011, 013, 015, 017, 018, 025, 026, 027, 032, 034, and 041; reworded verbiage in 2 nd paragraph in CDR 014; Changed verbiage of 8 th bullet in CDR 016 and 9 th bullet in CDR 017; "With each shipment" deleted from CDR 018, 019, 020, and 021; Deleted the 2 nd bullet in CDR 023; Added the last sentence in CDR 025; Changed/added several things in CDR 034 (please take careful note); Changed verbiage in B. Marking paragraph of CDR 044; Removed "defined in SQAM paragraph 8.3" in CDR 055; Addition of verbiage to last sentence of 3 rd paragraph in CDR 057, 058, 059, 060 as well as changes and additions to the 4 th paragraph.		
10	02/08/2017	Define document submittal requirements; Added CDRs 084 and 085, corrected several typo's and made minor corrections to the verbiage in the document	Tom Frazho / Anthony Conley	BPMS-03252
11	10/23/2017	Added 012 Flammability, changed 019 to 019A and added 019B Material Process Samples, added 029 Serialization, added 030A Approved Special Process (BAE), added 030B Approved Special Process (Customer), added 042 SPC Program, added 053 Dock to Stock Eligibility, changed 055 to 054, changed 056 to 055, added 056 PPAP Level I, added 086 Counterfeit Material Program and update 034 to remove requirement for micro hardness. Added verbiage to CDR 020, C.	Tom Frazho Richard Zuniga Ken Sturm Rosario Sciortino	BPMS-03819
12	06/20/2018	CDR 004 removed "and SHALL shall be approved by BAE Systems", 005 Added "for Combat Vehicles and Form 089559 for Weapon Systems", Added 007 A Welding Combat Vehicles Inspection Criteria for Armor Steel, 084 Removed from Item A & B "and approved", 085 Removed "and approved", 086 added This requirement is applicable to Phoenix for hardware and electronic purchases	James Dolan, Tom Frazho, Richard Zunga, Kenneth Sturm, Rosario Sciortino	BPMS-04027

		and to Combat Vehicles for electronic purchases only." Added/changed verbiage to CDR 032		
13	03/25/2019	Added verbiage, "paragraph 8.12" to the following CDRs: 001, 003, 004, 005, 011, 012, 013, 015, 016, 017, 018, 020, 025, 026, 027, 032, 033, 034, 041, 057, 058, 059, 060, 084, 085 Added "and documented" to 007A and 008 Added "prior to" to 014, 016, 017, 018, 020, 033, 034 Added "or with the" to 015, 016, 017, 018, 020, 033, 034 Added "shipment of product" to 015, 016, 017, 018, 020, 033, 034 Added "and bake the temperature and time values" to 016 Added "for this part" to 032, 034, 084, 085 Changed 034 firing records from aluminum forgings to just forgings and reworded the whole section	James Dolan, Tom Frazho, Richard Zunga, Kenneth Sturm, Rosario Sciortino	BPMS-04525
14	02/17/2020	Reformatted the fonts, and footer on all pages. Added CDR 042 back into document, 021B added, approved requirements added to many sections, rewrote CDRs, 003, 004, 034, 041A, added the Sterling Height Cage Code.	James Dolan, Tom Frazho, Ryan Cunningham, Kenneth Sturm, Rosario Sciortino, Ross Davis, William Slocomb	BPMS-05098
15	04/08/2021	Added 1 st sentence in 003 and 004, added VIR form number and added verbiage to 004, deleted reference to Combat Vehicles and Weapons Systems in 005, completely changed verbiage in 007, added 007B, changed document number from KA-021 to 091721 in 008, completely changed 016, changed verbiage in 023, added 026A, added 030C, changed verbiage throughout 034, changed VIR form number to 089725 in 057, changed to DFMEA & PFMEA in 058 as well as various verbiage, added new bullets to the beginning of 059	James Dolan, Tom Frazho, Ryan Cunningham, Kenneth Sturm, Mike Luciow, Ross Davis, William Slocomb	BPMS-06437
16	01/19/2022	001: Added, deleted and changed verbiage 004: Added, deleted and changed verbiage 007: Added, deleted and changed verbiage	James Dolan, Tom Frazho, Scott Heyd, Kenneth	BPMS-06999

		012: Added and changed verbiage 015: Added verbiage 016: Added and deleted verbiage 017: Added verbiage 019A: Deleted verbiage 021A & 021B: Added to the table of contents 026A: Added and deleted verbiage 027: Added and deleted verbiage 028: Added and deleted verbiage 030A: Added verbiage 030B: Added verbiage 030C: Added to the table of contents 041: Added and changed verbiage 042: Added, changed and deleted verbiage 068: Added to the table of contents 044: Deleted C and moved D up to C	Sturm, Mike Luciow, Ross Davis, William Slocomb	
17	02/07/2023	001: Added, These specified...added Revision to part number (second bullet), added /Lot Number/Identifier as applicable (third bullet) 004, 005, 006: Added minor changes 007: Deleted the first paragraph, made minor changes throughout and removed obsolete documents 007A, 017,020: Made minor changes, removed obsolete specification 015: revised clarified submittal requests 016: Updated for new ASTM B633 requirements and made minor changes to other paragraphs 018: Added traceability requirement and raw material request 023: Added CDR numbers 028: made minor changes 030A& 030B: Reformatted & removed last sentence and moved Phoenix to title 030D: Added paragraph 032: Made minor changes 034: added a new supplier Supplier template for armor products, corrected DLT to DTL and added dash 046: New 060: Minor changes/ formatted	James Dolan, Randy Fawver	BPMS-07705

		086: Minor changes, updated wording Table of Contents: renumbered & made minor formatting and corrections throughout the document.		
18	4/25/2023	005: Updated verbiage 007 / 007B / 008: Revised (clarified) 013: Approval clarification 018: Clarification 022A: Added for traceability for VPM 030E: New CDR for high strength fasteners 034: clarified thickness reduction criteria 085: Re-added Preface added Footer revision level, grammatical updates	James Dolan, Randy Fawver	BPMS-07898
19	07/13/2023	007A updated verbiage for Hybrid Weld codes. Addition of E & A to CDR 030E	James Dolan, Randy Fawver	BPMS-08039
20	9/3/2024	Updated header revision level Updated cover revision and date Added documentation delivery requirements under Preface Updated for various grammatical changes throughout document 001 Updated verbiage 003 Added submittal timing requirements 004 Updated verbiage, added submittal timing requirements 004A Added for TRR requirements 005 Updated verbiage 006 updated to allow flexibility for GSS review 007, 007A, 008 updated version 008A added 009 Removed 010, 011, 012 Updated submittal requirements 013 Removed 3 day document delivery requirements 014 Removed prior to shipment added QTY of parts, certification requirements 015 Restructured 016 Added BAE 017 Removed CARC painter submittal paragraph, removed or with product	James Dolan Scott Heyd Justin Shirley David Pearl Ken Sturm Matt Jones	BPMS-08823

		018 Added affirmation of DFAR compliance; Clarified submittal location 020 Updated 020A, 020B etc. format 022A Updated format and removed photographic requirements 026 Updated submittal requirements 026A Removed 027 Updated submittal information 029 Added provision of compliance to EB5638 030C Updated submittal requirements <u>030F Addition of High Strength Fastener requirements for Naval Products</u> 032 Updated submission requirements 034 Updated submission requirements, DFAR affirmation and certification level 036 New CDR for Reach 041 Removal of hardness critical 041A Added hardness critical 045 Removed CDR 056 through 060 Updated submittal requirements 084 Updated submittal requirements 085 Added submittal timing requirements 087 Added for Phoenix		
21	05/15/2025	Removed 'for this item' from CDR Manual Preface Added CDRs: CDR 022B Material Traceability CDR 090 Lot Homogeneity CDR 091 Sampling Method CDR 092 ADC CDR 092A ABCL CDR 004A Removed "All data submissions SHALL shall be per SQAM 8.12 Data Submission Instructions"; Moved TRR to end of heading. Added 007 Welding/Brazing-Combat Vehicles to contents CDR 012 removed Phoenix only reference CDR 017 Removed "Anniston Spares" language CDR 018 removed "252.225-7008" and added material certifications language. CDR 022A Added Tubes after VPM in the section title; Removed Hull Code ID	James Dolan Scott Heyd	BPMS-09227

Formatted: Font: 10 pt

Formatted: Font: 10 pt

		CDR 30E Changed verbiage in 2 nd paragraph; changed to lower case font CDR 032 Changed "Purchasing" to "Supplier" for reference to website. CDR 034 Added Material Certifications language to last paragraph CDR066 Removed CAGE Code Anniston Aftermarket Spares. CDR067 Removed CAGE Code Anniston Forge CDR 086 Changed reference from Combat Vehicles to CMS; this referenced sentence moved from the beginning of the CDR to the last sentence of the CDR		
22	09/14/2026	<u>Updated cover sheet to meet company branding requirements</u> <u>Updated Preface and reduced all SHALL statements to shall</u> <u>Updated Table A, removed CDR 022, 037, 053, 065, 066, 067. Added 023A and B, 024, 041A, 042, 061.</u> <u>Updated CDR 001 per Inc project</u> <u>Rewrote CDR 003 to adapt INC AS9102 requirements but allow flexibility for CMS</u> <u>Updated CDR 004 language to align to PQSE needs</u> <u>Updated CDR 004A language to align to PQSE needs</u> <u>Updated CDR 005 per Inc project</u> <u>Added CDR 005A per Inc project</u> <u>Updated CDR 006 per Inc project</u> <u>Updated CDR 007A to remove specification language and add customer approved platform and as directed by Purchase Order</u> <u>Added CDR 009 Solder Approval back in</u> <u>Updated CDR 010 per Inc project</u> <u>Updated CDR 013 per BAE level 3 NDT guidance</u> <u>Updated CDR 014 per Inc project</u> <u>Updated CDR 016 to require material certs</u> <u>Updated CDR 017 to include salt spray test and blast profile data</u> <u>Updated CDR 018 per Inc project</u>	<u>Matt Hoekstra</u> <u>Scott Heyd</u> <u>George Gilbert</u> <u>Justin Shirley</u> <u>Gabe Gomez</u> <u>Michelle Fisher</u> <u>Adewumi Bakare</u>	<u>BMS-00809</u>

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

		<u>Eliminated CDR 020 A-G and wrote a one single CDR 020 requirement</u> <u>Updated CDR 021A per Inc project</u> <u>Updated CDR 022 per Inc project</u> <u>Updated CDR 022A per Weapon Systems guidance</u> <u>Updated CDR 022B per Weapon Systems guidance</u> <u>Updated CDR 023A and 023B per Inc project,</u> <u>deleted CDR 023C and 023D</u> <u>Eliminated CDR 023C and 023D</u> <u>Updated CDR 027 per Inc project</u> <u>Updated CDR 029 per Inc project</u> <u>Updated CDR 034 per Materials Engineering guidance</u> <u>Updated CDR 036 per Inc project</u> <u>Deleted CDR 037</u> <u>Updated CDR 042 per Inc project</u> <u>Deleted CDR 53</u> <u>Deleted CDR 65</u> <u>Updated CDR 085 per Inc project</u> <u>Updated CDR 086 and split into CDR 086A and 086 B per Inc project</u> <u>Added CDR 093 Product Risk Management (PRM)</u> <u>Updated CDR 090, 091, 092, 092A per HVP guidance</u>		
--	--	---	--	--

Formatted: Font: 9 pt, Not Bold, Font color: Text 2

Formatted: Caption

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Space After: 0 pt, Line spacing: single

Preface

The Supplier is required to adhere to assigned Contract Deliverable Requirements (CDRs) on the PO and deliver the requested objective evidence per the data submission instructions and CDR specific requirements. The Supplier ~~is required to meet and shall~~ have available objective evidence to all other SQAM, PO and TDP requirements as applicable available upon request. Requests for records ~~SHALL shall~~ be fulfilled within five (5) business days. BAE Systems strongly advises all Suppliers to consider documentation submittal and BAE System's review and approval times into your schedule and BAE System's promise dates.

All CDRs in this manual (outside of the CDRs in table A below) SHALL have documentation submitted and approved prior to shipment of the item (s) in accordance with the data submission instructions located in the Supplier Quality Assurance Manual (SQAM) Section 8.12. ~~The Supplier SHALL NOT for all CMS locations. Documentation for Phoenix orders only, are shipped with product and do not need submitted electronically prior to shipment. The Supplier shall not~~ ship without an approved Vendor Information Request (VIR), waiving any CDRs they are unable to meet. Shipment without BAE System's approval constitutes the material as non-conforming. For any CDR submittal where the documentation covers the whole PO order quantity, identify this on form 092245.

For CDRs outside of table A, payment may be predicated on submittal and approval, prior to shipment.

Table A: CDRs that do not require submittal:

CDR-022 <u>023 A</u> and B	CDR-023 <u>024</u>	CDR-026	CDR-028	CDR-030A	CDR-030B
CDR-030D	CDR-037 <u>041A</u>	CDR-044 <u>042</u>	CDR-046 <u>044</u>	CDR-053 <u>046</u>	CDR-054
CDR-055	CDR-064 <u>061</u>	CDR-065 <u>064</u>	CDR-066 <u>068</u>	CDR-067 <u>083</u>	CDR-068 <u>087</u>
CDR-083	CDR-087				

Formatted Table

Formatted: Normal, Tab stops: Not at 0.97" + 1.46"

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Contents

001 Inspection/Test Data Reports12

003 First Piece Inspection Report12

004 First Article Test (FAT).....12

004A Test Readiness Review (TRR).....12

005 Customer Source Surveillance (CSS).....13

006 Government Source Surveillance/Inspection (GSS/GSI).....13

007 Welding/Brazing Combat Vehicles.....14

007A Welding Combat Vehicles Inspection Criteria15

007B Welding Combat Vehicles: Additional Weld Requirements16

008 Welding/Brazing Weapon Systems.....17

008A Welding/Brazing Procedures Requiring NAVSEA Approval.....18

010 Solderability.....19

011 Printed Wiring Boards (PWB).....19

012 Flammability.....19

013 Nondestructive Examination Procedures.....19

014 Nondestructive Examination Inspection Report.....20

015 Control Tests.....20

016 Plating21

017 Paint Certification.....22

018 Physical and Chemical Test Reports23

019A Test Samples — Tensile Testing23

019B Material/Process Samples.....23

020 A-G Heat Treating23

020A Visual Metallographic Inspection23

020B Quench and Temper (Core Hardness Specified).....24

020C Quench and Temper (Surface Hardness Specified, Core Hardness Not Specified).....24

020D Case Hardening — Carburizing24

020E Case Hardening — Nitriding24

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

020F Surface Hardening—Flame or Induction.....25

020G Stress Relief25

021A Mercury25

021B Lead.....25

022 Material Traceability.....25

022A Material Traceability—Weapon Systems—VPM Tubes25

022B Material Traceability—Weapon Systems—Submarine Box Parts ..26

023 Age Control.....26

024 Non-manufactured Coniferous Wood Products27

025 Special Packaging.....27

026 Quality Requirements.....27

027 Certificate of Compliance27

028 Unique Identification (UID).....27

029 Serialization.....27

030A Phoenix Approved Special Processors (BAE Systems).....28

030B Phoenix Approved Special Processors (Customer).....28

030C NADCAP Approved Special Processes.....28

030D Combat Vehicles Approved Special Processors (BAE Systems).....28

030E High Strength Fasteners (HSF) for Naval Products28

032 Ballistic Requirements—Transparent Armor30

034 Ballistic Requirements—Metal and Composite Materials31

036 REACH Assessment.....39

037 CPNA (Critical Part Number Assessment) Assigned Item.....39

041 Critical Safety Items (CSI)40

041A Critical Safety Items (CSI) Heat Treat Supplier40

042 SPC Program.....40

044 Packaging Instructions for Hardware Kits.....40

046 QUALIFIED PRODUCT LIST (QPL).....42

053 Deck-To-Stock Eligibility42

054 AQL 1.043

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

055 100% Inspection.....43

056 PPAP Level 1.....43

057 PPAP Level 2.....43

058 PPAP Level 3.....44

059 PPAP Level 4-Predefined Requirements.....45

060 PPAP Level 4-Unique Requirements.....46

061 PPAP Level 5.....47

064 York CAGE Code.....47

065 San Jose CAGE Code.....47

068 Sterling Heights CAGE Code.....47

083 Electrostatic Discharge (ESD).....47

084 Process Failure Mode and Effects Analysis (PFMEA) and Control Plans (CP).....47

085 First Article Inspection.....49

086 Counterfeit Material Program.....49

087 Material Workmanship Standard.....49

090 Lot Homogeneity.....49

091 HVP Lot Sampling Method.....50

092 Ammunition Data Card (ADC).....50

092A As-Built Configuration List (ABCL).....50

001 Inspection / Test Data.....18

003 First Piece Inspection Report.....18

004 First Article Test (FAT).....18

004A Test Readiness Review.....18

005 Source Inspection.....19

005A In Process Source Inspection.....21

006 Government Source Inspection.....21

007 Welding/Brazing-Combat Vehicles.....22

007A Welding Combat Vehicles Inspection Criteria.....25

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

008 Welding/Brazing-Weapon Systems 26

008A Welding/Brazing-Procedures Requiring NAVSEA Approval 27

009 Soldering 28

010 Solderability..... 29

011 Printed Wiring Boards (PWB) 29

012 Flammability 29

013 Nondestructive Examination Procedures..... 29

014 Nondestructive Examination Certification 30

015 Control Tests..... 30

016 Plating 32

017 Paint Certification..... 33

018 Physical and Chemical Test Reports 34

019A Test Samples – Tensile Testing 34

019B Material/Process Sample..... 34

020 Heat Treating..... 35

021A Mercury Exclusion 37

021B Lead 37

022 Traceability 37

022A Material Traceability – Weapon Systems – VPM Tubes 37

022B Material Traceability – Weapon Systems – Submarine Box Parts .. 38

023A 75% Shelf Life / Limited Life Material (LLM) 38

023B 50% Shelf Life / Limited Life Material (LLM) 39

024 Non-manufactured Coniferous Wood Products 40

025 Special Packaging 40

026 Quality Requirements 40

027 Goods / Services Certificate of Conformance 40

028 Unique Identification (UID)..... 41

029 Serialization..... 41

030A Phoenix Approved Special Processors (BAE Systems)..... 41

030B Phoenix Approved Special Processors (Customer)..... 41

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

030C NADCAP Approved Special Processes 41

030D Combat Vehicles Approved Special Processors (BAE Systems) 42

030E High Strength Fasteners (HSF) for Naval Products “Zinc” 42

030F High Strength Fasteners (HSF) for Naval Products “Cadmium” 44

032 Ballistic Requirements-Transparent Armor 45

034 Ballistic Requirements- Metal and Composite Materials 46

036 REACH Assessment 55

041 Critical Safety Items (CSI) 56

041A Critical Safety Items (CSI) Heat Treat Supplier 56

042 SPC 56

044 Packaging Instructions for Hardware Kits..... 56

046 Qualified Product List (QPL) 59

054 AQL 1.0 59

055 100% Inspection 59

056 PPAP-Level 1..... 59

057 PPAP-Level 2..... 59

058 PPAP-Level 3..... 60

059 PPAP-Level 4-Predefined Requirements..... 61

060 PPAP-Level 4-Unique Requirements..... 62

061 PPAP-Level 5..... 63

064 York CAGE Code..... 63

068 Sterling Heights CAGE Code 63

083 Electrostatic Discharge (ESD)..... 63

084 Process Failure Mode and Effects Analysis (PFMEA) and Control Plans (CP)..... 63

085 First Article Inspection 64

086 Counterfeit Electronic Material COC 65

086A Counterfeit Material COC (Non-Electronic) 65

087 Material Workmanship Standard 66

090 Lot Homogeneity 66

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

091 HVP Lot Sampling Method 66

092 Ammunition Data Card (ADC)..... 67

092A As-Built Configuration List (ABCL) 67

093 Product Risk Management (PRM)..... 68

094 Obsolescence DMSMS Monitoring..... 68

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

001 Inspection / Test Data Reports

The Supplier of BAE Systems SHALL submit forshall provide with each piece. All the Supplier's actualshipment inspection/ and / or test data for the specified characteristics identified and specifiedas required per the purchase order. 100% of each piece in the lot shall be inspected and / or tested unless otherwise stated in the purchasing agreement. If your purchasing purchase order. Inspection agreement does not clarify specific inspection or test data requirements, contact your Purchasing Representative for direction, or a full FPI for each piece, as required per SQAM 8.3. shall be provided with each shipment. Any deviations of data reported from the purchase order requirements shall be approved by BAE Systems prior to shipment.

003 First Piece Inspection Report

The Supplier SHALL submit theirshall complete a First Piece Inspection (FPI) report as specifiedIn Accordance With (IAW) the latest revision of SAE AS9102 on the entire Technical Data Package (TDP) and contractual requirements following the remaining provisions of CDR 085 below.

The FPI shall only be required in the SQAM paragraph 8.3. event the following conditions occur:

- No previous CDR 003 was submitted and approved by BAE Systems
- A new or delta First Article Inspection (FAI) is required per the provisions stipulated in SAE AS9102

004 First Article Test (FAT)

FAT is required to validate that the production processes are producing results within specification (s). Suppliers are required to inform BAE Systems, using VIR form 089725 when any of the following situations occur, prior to shipment, to determine what additional testing is required:

- 1.) Change in the manufacturing process at tier 1 or any sub-tier Suppliers (BAE Systems is to be notified prior to the change (s) being made)
- 2.) Drawing changes provided by BAE Systems or any/all Suppliers Supplier controlled drawing changes
- 3.) Manufacturing location change at tier 1 or any sub-tier Suppliers (BAE Systems is to be notified prior to the change (s) being made)
- 4.) Break in production of 24 months or more at tier 1 or any sub-tier Suppliers.

The procedure and test reports may be prepared using MIL-HDBK-831 as a guide. BAE Systems and its customer reserve the right to witness FAT at any point in the schedule.

For the initial FAT, the Supplier SHALLshall create and submit the FAT plan within 30 business days following the contract award. and shall not perform FAT testing until BAE Systems approves the FAT plan. For delta FAT testing, the Supplier SHALLshall create and submit the delta FAT plan within 30 business days following the identified need of delta FAT. Supplier SHALL and shall not perform DFAT testing until BAE systems approves the DFAT plan. The supplier, shall notify BAE Systems a minimum of 15 business days prior to start of testing. The FAT report SHALLshall be submitted a minimum of 15 business days prior to shipment and approved by BAE Systems. before shipment.

004A Test Readiness Review (TRR)

TRR is required for this part and is conducted to increase the probability of success during 'formal' testing. The review ensures the maturity of the test article (s), the test documentation and the test

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Line spacing: single

Formatted: Line spacing: single, Don't keep lines together

Formatted: Font: +Headings (Cambria), 12 pt, Font color: Accent 1

Formatted: Line spacing: single

Formatted: Line spacing: single

Formatted: Line spacing: single

Formatted: Line spacing: single

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

environment prior to initiating formal testing. The TRR acceptance Testing Plan (ATP) verifies, from a test perspective, that the proper level of preparation is complete, the required coordination has been completed and that the resources are adequately planned to support the test objectives. The supplier is responsible for coordinating TRR with BAE Systems and as if required BAE Systems will include the US Government. Advanced notification of 15 days is expected to coordinate review. The review may proposed ATP shall be held virtually or at the Supplier's facility.

A TRR will be conducted before submitted and approved a minimum of thirty (30) days before each FAT/DFAT and formally presented in slide deck form to BAE Systems prior to the start of testing (First Article Test) / DFAT (Design First Article Test) or as required by purchase order.

The TRR may consist ATP consists of, but not limited to:

- LRU/Unit name
- Test (s) being performed
- Step by step method of test
- Test Schedule including set-up, breakdown, shipping times, test duration (s)
- Quantities of LRU/sunits undergoing testing
- Test Location (s)
- Test Objectives
- Test Parameters
- Test Limitations (if any)
- Test Readiness Criteria Including
 - Test Plan
 - Required Test Asset Availability and Status
 - Test Equipment Availability and calibration status
 - Test Support Personnel
 - Provisions for recording results of each required performance in a clear and concise form.
 - Schematic of required test fixtures shall be supplied when referenced in procedure.
 - Critical for unit acceptance
 - Safety Requirements
 - Disposition
 - Test readiness criteria includes the following:
 - Test plan
 - Test asset availability and status
 - Test equipment availability and status
 - Test support personnel (EX: contractor and Test House Names, contact information)
 - Contractor and Test House document that certifies test procedure is understood and that all equipment (owned and rented) is readily available when scheduled
 - Contractor and test house document that certifies all personnel executing the test has been trained (training matrix, training certificate, training record)
 - Design variance (e.g., Request for Variance (RFV)) sign off (if applicable)
 - Test procedure/profile variance to contract (ex RFV) sign off (if applicable)

005 Customer Source Surveillance (CSS) Inspection

Source surveillance, inspection, and/or test Inspection is required prior to product shipment. Visits will be conducted by a BAE Systems Quality Assurance representatives, their delegate(s), and/or their subject matter experts. Source inspections may be witnessed by BAE Systems customers or government

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Font color: Auto

Formatted: Font color: Auto

Formatted: Font color: Auto

Formatted: Font color: Auto

Formatted: Font color: Auto

Formatted: Font color: Auto

Formatted: Font color: Auto

Formatted: Font color: Auto

Formatted: Space After: 0 pt, Font Alignment: Auto, Pattern: Clear

Formatted: Font color: Auto

Formatted: Font color: Auto

Formatted: Font color: Auto

Formatted: Space After: 0 pt, Font Alignment: Auto, Pattern: Clear

Formatted: Line spacing: single

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

representatives. Visits may be conducted once or multiple times (concurrently or individually) at the Supplier's premises.

Unauthorized/unapproved shipment (without completed source inspection representative is required for each shipment of this item. The product SHALL be presented with all required contract or TDP.) is cause for rejection and may result in a Supplier Corrective Action Request and/or product return at the Supplier's expense and withholding of the invoice payment. Note: BAE Systems Quality Assurance reserves the right to waive the source inspection.

The Supplier shall track schedule progress and notify BAE Systems a minimum of 5 business days in advance of any source-inspection milestone.

The Supplier shall ensure purchase order requirements are met prior to presentation. In order to accommodate BAE System's source inspection representatives, the activities, any identified non-conformances found during source inspection may result in rejection and or corrective action.

The Supplier SHALL make shall provide all reasonable facilities and equipment available (including internet access, telephone, and workspace) to support BAE Systems personnel and assist in a safe and convenient performance of these visits.

The Supplier shall provide the following for each source inspection. The following:

- Purchase order and applicable change notices
- Variances or deviations to the purchase order
- Current drawings, specifications, procedures and related documentation SHALL be presented to
- Inspection / test reports showing compliance to purchase order requirements
- Subcontract / purchase order data items (e.g., Acceptance or Qualification Test Procedure)

The Supplier shall have ready if requested by the source inspector:

- A copy of the current PO
- Variances and or completed VIRs attached to PO
- Current CQR (Configuration Quality Requirements) attached to PO
- All drawings defined on CQR
- Inspection records
- OQE supporting CDR / drawing requirements on PO

Formatted: Space After: 0 pt, Line spacing: single

The Supplier SHALL provide a minimum five (5) business working days advance notification of requests for source inspection through submission of Form 092245. Unauthorized/unapproved shipment of product without a BAE Systems source inspection is cause for rejection, a Supplier corrective action request may be issued and product may be returned to the Supplier at the Supplier's expense and withholding of the invoice payment.

- Manufacturing, planning, traveler, and/or supplemental documents
- Qualification test approval letter
- First Article approval
- Supplier subject matter experts (to support technical evaluation)

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Line spacing: single

Note: If parts are returned for repair ~~or~~, rework, ~~or replacement~~ a resubmission of source inspection is required. ~~Parts are not to be shipped until the resubmission for source inspection has been approved and the source form is annotated with 'Repair or Rework' and lists the NCR number on the form.~~

Note: Form 092245 shall be utilized to request source inspection. BAE Systems will schedule source inspection 5 to 10 days upon receipt of source request. The Supplier will incur a cancellation fee and Supplier rating impact in the event they cannot support the source activity.

005A In Process Source Inspection

An in process inspection is required prior to product shipment. Visits will be conducted by BAE Systems Quality Assurance representatives, their delegate(s), and/or their subject matter experts during specific manufacturing or test stages. Source inspections may be witnessed by BAE Systems customers or government representatives. Visits may be conducted once or multiple times (concurrently or individually) at the Supplier's premises. Visits will be coordinated mutually between BAE Systems and the Supplier and will be detailed in the purchase order.

Unauthorized/unapproved shipment (without completed in process source inspection) is cause for rejection and may result in a Supplier Corrective Action Request and/or product return at the Supplier's expense and withholding of the invoice payment.

Note: BAE Systems Quality Assurance reserves the right to waive the source inspection. The Supplier shall track schedule progress and notify BAE Systems a minimum of 5 business days in advance of agreed upon in process source-inspection milestone (s).

Note: Form 092245 shall be utilized for source inspection requests.

006 Government Source Inspection

Government Source Inspection (GSI) / Government Source Surveillance/Inspection (GSS/GSI)

Formatted: Font: 12 pt, Font color: Custom Color(61,65,70))

(gSI) is required on this purchase order. Upon receipt of this order the Purchasing Agreement, supplier shall promptly notify the Government your government representative who normally services your facility so that appropriate planning for Government inspection can be completed. If the local can be accomplished. Each shipment on this purchase order shall be accompanied with objective evidence of agreed to government witness and/or inspections and provided per the purchase order data submission instructions.

Formatted: Font color: Custom Color(61,65,70))

Formatted: Font color: Custom Color(61,65,70))

Formatted: Font color: Custom Color(61,65,70))

Formatted: Font color: Custom Color(61,65,70))

Formatted: Font color: Custom Color(61,65,70))

The Supplier shall provide all reasonable facilities and equipment to Government representative directs the source surveillance/inspection should take place at a sub-tier Supplier facility, the full wording of this requirement SHALL be incorporated into the Purchasing Agreement with that sub-tier Supplier. The text of this requirement may be incorporated by reference. At no time SHALL the Supplier flow any Government source surveillance/inspection requirements to their sub-tier Suppliers without the direction of their local Government representative personnel and assist in a safe and convenient performance of these visits. The Supplier shall provide all drawings, specifications, procedures and related test data required for performance of the inspection.

Formatted: Font color: Custom Color(61,65,70))

Formatted: Space After: 10 pt, Line spacing: single, Don't keep with next, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Font color: Custom Color(61,65,70))

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt
Formatted: Font: 10 pt

Unauthorized shipment of product without Government Source Surveillance is cause for rejection and subsequent return at the Suppliers' cost and withholding of the invoice payment. GSS SHALL not replace Supplier inspection nor relieve the Supplier of its responsibility to meet all requirements of the Purchasing Agreement.

Supplier must notify BAE Systems prior to, or in conjunction with, notification to the Defense Contract Management Agency (DCMA) so that BAE Systems has the opportunity to can schedule and perform any reviews/inspections prior to submission to DCMA.

Formatted: Font color: Custom Color(61,65,70))
Formatted: Normal, Line spacing: single, Don't keep with next
Formatted: Font color: Custom Color(61,65,70))
Formatted: Font color: Custom Color(61,65,70))
Formatted: Font color: Custom Color(61,65,70))

The Supplier SHALL notify the local Government DCMA Representative of pending inspections in accordance with FAR 52.246-2(i) (2), at:

For DCMA notification and coordination activities reference the DCMA website guidance. [52.246-2 Inspection of Supplies-Fixed-Price. | Acquisition.GOV](#)
The Supplier SHALL submit evidence of GSS review with each shipment.

Formatted: Font color: Custom Color(61,65,70))

007 Welding/Brazing-Combat Vehicles

CDR007 shall be submitted and approved PRIOR to the start of fabrication, the Supplier SHALL submit and gain approval for all procedure (s) per the PO Purchase Order Part Number. Unless otherwise specified and/or prohibited by the applicable PO, Contract, Drawing, and/or Specification, authorized Suppliers MAY may utilize BAE Systems Weld Procedure Specification (s) (WPS) in the event that if the Supplier has received authorization by completing the BAE Systems required Weld Procedure Training and subsequent Weld Process Audit.

Formatted: Font color: Text 1
Formatted: Font: Not Bold

NOTE: Suppliers may utilize BAE Systems Weld Procedures under the Hybrid Weld Codes 4399307 and 4399308. However, under the Hybrid Weld Code Steel (4399307) Section 4.5.4.2 Procedure Transfers, the Supplier SHALL create a validation test plate using the WPS parameters to qualify for welding with the WPS in accordance with Section 4.6 Welder Performance Qualification to demonstrate the entity is capable of meeting the requirements of the transferred WPS. This validation test is ONLY to be performed for each BAE Systems Steel Weld Procedure utilized under the Hybrid Weld Code Steel (4399307).

Formatted: Font color: Black

NOTE: CDR007 submittals-Note: The BAE Systems Weld Procedures available for use may vary by Contract and be limited to the Weld Procedures reviewed and approved by BAE Systems' Customer.

Suppliers who choose to utilize STEEL weld procedures contained in CDRL A036 shall perform a validation test plate in accordance with Mil-STD-3040 and/or Mil-STD-3057, along with subsequent document revisions, strictly prohibit the use of the requirements detailed in 4399307- Arc Welding of Steel for Combat Vehicles.

In the event the Supplier provides a STEEL BAE Systems Weld Procedures for Weld Classes II, III, and IV. For POs, contracts, and/or drawings requiring welding in accordance with Mil-STD-3040 and/or Mil-STD-3057 qualified Weld Procedure that is contained within CDRL A036, the Supplier SHALL qualify and provide Weld Procedure(s) and supportingshall submit the following

Formatted: Font: Arial, 10 pt
Formatted: Font: Arial, 10 pt
Formatted: Font: Arial, 10 pt
Formatted: Font: Arial, Italic
Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

documentation in accordance with the requirements listed in, as required per 4399307- Arc Welding of Steel for Combat Vehicles, to verify that the validation was performed:

- A Welder Performance Qualification (WPQ) stating the applicable specification--BAE Systems STEEL Weld Procedure with all necessary essential variables and testing performed.

In the event the Supplier is ~~NOT~~not authorized to utilize BAE Systems Weld Procedures and/or BAE Systems ~~DOES NOT~~does not have applicable Weld/Braze Procedure (s) to fabricate the Weldment/Brazement to fulfill the PO, the Supplier ~~SHALL~~shall be responsible for providing and/or qualifying Weld/Braze Procedure (s), in accordance with the specified code, ~~PRIOR~~prior to fabrication. BAE Systems Weld Engineering ~~SHALL NOT~~shall not be responsible for providing additional procedure qualifications for the sole use of our Suppliers.

Formatted: Font: Arial

Formatted: Body Text, Indent: Left: 0.29", Right: 0.43", Line spacing: single, Tab stops: Not at 2.81"

Formatted: Font: 11 pt

In the event 4399307- Arc Welding of Steel for Combat Vehicles and/or 4399308-Arc Welding of Aluminum for Combat Vehicles is required, Suppliers may leverage the following codes for procedure qualifications under this requirement as permitted by the applicable Contract:

MIL-STD-3040A	ABS 1 Part 2	AWS D9.1/D9.1M
MIL-STD-3057	ABS 14	SAE AMS2680
AWS D1.1/D1.1M	ABS 165	SAE AMS2681
AWS D1.2/D1.2M	ABS 186	AWS D14.0/D14.0M
AWS D1.3/D1.3M	ABS 302	AWS D14.6/D14.6M
AWS D1.6/D1.6M	S9074-AQ-GIB-010/248	AWS D14.9/D14.9M
AWS D1.9/D1.9M	S9086-CH-STM-010/CH-074V1	4399307
AWS D8.1M	S9074-AR-GIB-010/278	4399308
AWS D8.8M	T9074-ASGIB-010/271	AWS D17.1/D17.1M
AWS D8.10M	MIL-STD-1689	AWS D17.2/D17.2M
AWS D8.14M	SFLC Std Spec 0740	AWS D17.3/D17.3M
AASHTO/AWS D1.5M/D1.5	AWS B2.1/B2.1M	ASME Section IX
AWS D16.4M/D16.4	AWS C1.1M/C1.1	ASME Section VIII – Division 1
AWS QC19	AWS C1.4M/C1.4	ASME Section V
AWS C6.2/C6.2M	ASME B31.3	-

Formatted: Line spacing: single

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

The Supplier ~~SHALL~~shall submit the WPS/BPS(s) intended for part fabrication to BAE Systems Weld

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Engineering for review and approval via the CMS Supplier Weld/Braze Procedure Submission Form (BMS 089136) ~~PRIOR~~prior to the start of welding/brazing and fabrication. The latest version of the form ~~SHALL~~shall be utilized and is accessible via the BAE Systems CMS Supplier Website.

Each Weldment/Brazement part number and the applicable WPS/BPS(s) ~~SHALL~~shall be submitted individually.

In the event the Supplier provides a non-BAE Systems qualified Weld Procedure, or is not authorized to utilize BAE Systems Weld Procedures, the Supplier ~~SHALL~~shall submit the following documentation, as required per the applicable code and/or specification, ~~PRIOR~~prior to the start of welding/brazing and fabrication:

Formatted: Font: Bold

- ~~▲~~▲ Welding Procedure Specification (WPS)/Brazing Procedure Specification (BPS)
- ~~▲~~▲ Supporting Procedure Qualification Record (PQR)/ Brazing Procedure Qualification Record (BPQR)- to include non-destructive and destructive supporting test data
- ~~▲~~▲ Any additional supporting documentation that is required for submittal in accordance with the applicable drawing and/or specification

Formatted: Font: Not Bold, Font color: Auto

Formatted: Font color: Auto

Formatted: Font: Not Bold

Formatted: Font: Not Bold

All Weld procedures and/or Braze procedures to be utilized ~~SHALL~~shall be approved ~~PRIOR~~prior to use; which ~~SHALL~~shall include tack welding and/or rework. Supplying product to BAE Systems with an unapproved, rejected, and/or incorrect WPS/BPS is a violation of the BAE Systems Purchasing Agreement and SQAM and ~~SHALL~~shall be considered non-conforming.

The Supplier ~~SHALL~~shall be responsible for resubmitting the form ~~in the event that if~~ any changes in base material, Weld/Braze procedure (s), the part number configuration, and/or any other changes ~~or~~ revisions that impact the Welding/Brazing processes and/or procedures from the previously approved submittal. The form ~~SHALL~~shall be resubmitted if the BAE Systems Purchasing Order part number changes throughout configuration, regardless if all other variables have remained consistent from the previous approval.

~~NOTE: The processes and procedures that are to be used in fabrication SHALL directly align with the latest CDR007 approval on record. Should the Supplier resubmit and gain approval on the PO part number and Weldment/Brazement part number combination, any shall supersede all previous CDR007 approvals containing that specific combination are superseded by the most recent approval. Example: If the Supplier has a previously approved process (GMAW) and wishes to add an additional process (GTAW), both procedures and processes must be included in the resubmittal if they are intended to be used on the subject part.~~

Formatted: Font: Not Italic

Formatted: Strikethrough

The Supplier ~~SHALL~~shall be responsible for maintaining all supporting documentation including, but ~~NOT~~not limited, to the following: procedure qualifications, performance qualifications, sub-tier ~~supplier~~Supplier certifications, machine calibration documentation, and other applicable documentation required to demonstrate compliance in accordance with the requirements per the BAE Systems Purchasing Agreement. All documentation ~~SHALL~~shall be made available, as requested, to BAE Systems at all times.

For weld repairs and/or clarifications regarding weld/braze drawing requirements, the Supplier ~~SHALL~~shall submit a Vendor Information Request (VIR) Form (BMS 097908) for review and disposition ~~PRIOR~~prior to use.

Formatted: Line spacing: single

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

007A Welding Combat Vehicles Inspection Criteria

Visual Testing (VT) ~~SHALL~~shall be completed and documented on 100% of all welds. The Certificate of Conformance (CoC) Weld Certification form 090475 ~~SHALL~~shall be submitted with **all shipments**. BAE requests for the Certified Weld Inspector (CWI), Senior Certified Weld Inspector (SCWI) or Canadian Welding Bureau (CWB) to stamp the COC with their AWS or CWB credentials. For the **first shipment**, the First Submission Weld Roadmap Form 091460 ~~SHALL~~shall also be included with the CoC Weld Certification Form.

Formatted: Indent: Left: 0", Line spacing: single

All Visual Testing (VT) ~~SHALL~~shall be conducted by one of the following certification platforms:

- An American Welding Society ~~Certified Welding Inspector~~(CWI) and/or ~~Senior Certified Welding Inspector~~(SCWI)
- A qualified CWB Level 2 or 3 through the Canadian Welding Bureau, as determined through the Canadian Standards Association-
 - ~~Other certifications, as defined by the applicable weld code and/or specification~~
- A Government approved certification platform, evidence of approval shall accompany form 090475
- As directed per the Purchase Order

All ~~Visual Testing (VT)~~ on armor steel and/or quenched and tempered steel ~~SHALL~~shall be held for 48 hours PRIOR to final inspection. When Non Destructive Testing (NDT) is required per the drawing, all welded high strength steels including, but not limited to, armor steel and low alloy steels 90 KSI (620MPa) in tensile strength or greater ~~SHALL~~shall be held a minimum of 48 hours PRIOR to NDT inspection.

Formatted: Indent: Left: 0", Line spacing: single

~~007B Welding Combat Vehicles: Additional Weld Requirements~~

~~The Supplier SHALL reference the applicable Code and/or Specification designated by the applicable PO, Contract, and/or Drawing and its entirety. The Supplier SHALL be responsible for reviewing AND adhering to ALL requirements listed in the designated Weld Code.~~

~~Aluminum:~~

~~In addition to the requirements specified in CDR007 Welding Combat Vehicles, the following requirements have updated within the specified Weld Code:~~

- ~~Weld Procedure Qualifications: the requirements for utilizing Multiple Welding Processes within a single procedure~~
- ~~Operator Qualifications: the requirements for the Number of Electrodes an Operator is qualified to utilize~~

~~Steel:~~

~~In addition to the requirements specified in CDR007 Welding Combat Vehicles, the following requirements have updated within the specified Weld Code:~~

- ~~Weld Procedure Qualifications: the requirements for Preheat/Interpass Temperature, Travel Speed, Heat Input, and Charpy V Notch (CVN) Testing have updated~~

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

- Non-Destructive Testing (NDT): Following welding, for all high strength steels and armor grade steels greater than 0.25" (6mm) in thickness, the final NDT examination for acceptance SHALL be conducted no less than 48 hours after the final weld has cooled to ambient temperature. Preliminary NDT examinations are advisable to avoid production related delays by identifying defects not related to delayed hydrogen cracking. These defects can be addressed before the 48-hour hold is complete, restarting the 48-hour period. Defects identified and addressed following the first 48-hour hold SHALL be subject to an additional 48-hour hold. Alternative strategies to mitigate delayed hydrogen cracking must be supported by data and SHALL be submitted to the procuring activity for review for acceptability prior to amending the length of this hold time.
- Procedure Transfers: It is allowable to transfer qualified and approved welding procedure (s) between an entity and its sub-entities, for all classes of welds. The receiving transferee (Supplier and/or Sub-Tier Weld Supplier/Fabricator) SHALL create an initial validation test plate using the WPS parameters to qualify for welding with the WPS in accordance with the applicable Weld Code.
 - The sub-entity SHALL submit the BAE Systems Validation Test Plate Data Sheet and document the applicable information as required. Failure to provide the necessary information SHALL result in the ineligibility to utilize the entity's Weld Procedure(s).
 - A re-validation test MAY be required to demonstrate that the sub-entity is capable of adhering to the requirements specified in accordance with the Weld Procedure in question, as a result of the following events:
 - Non-conformance (s) identified during a Weld Process Audit conducted by BAE Systems' Supplier Quality Team
 - Non-conforming welded part (s) received by BAE Systems

008 Welding/Brazing-Weapon Systems

PRIOR to the start of fabrication, the Supplier SHALL submit and gain approval for all procedure(s) per the PO Purchase Order Part Number. The Supplier SHALL be responsible for qualifying and providing Weld/Braze Procedure (s) PRIOR to fabrication. The Supplier SHALL submit the following documentation, as required per the applicable code and/or specification, to BAE Systems for review and approval via the CMS Supplier Weld/Braze Procedure Submission Form (BMS 089136) accessible via the BAE Systems CMS Supplier Website, PRIOR to the start of welding/brazing and fabrication:

- Welding Procedure Specification (WPS)/Brazing Procedure Specification (BPS)
- Supporting Procedure Qualification Record (PQR)/ Brazing Procedure Qualification Record (BPQR)- to include Non-Destructive and Destructive Supporting Test Data
- Personnel Performance Qualifications*- to include a minimum of 1 Welder/Welder Operator Performance Qualification (WPQ) and Brazer/Braze Operator Performance Qualification (BPQ) *submittals ONLY required for personnel executing the respective welding and/or brazing operations to cover the entire scope of work
- Any additional supporting documentation that is required for submittal in accordance with applicable drawing and/or specification

Formatted: Font: Not Bold

Formatted: Font: Not Bold

Formatted: Font: Not Bold

Formatted: Font: Not Bold

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

All Weld/Braze Procedures to be utilized ~~SHALL~~shall be approved **PRIOR** to use; which ~~SHALL~~shall include tack welding and/or rework. Supplying product to BAE Systems with an unapproved, rejected, and/or incorrect WPS/BPS is a violation of the BAE Systems Purchasing Agreement and SQAM and ~~SHALL~~shall be considered non-conforming. All Weld Procedures and/or Braze Procedures to be utilized ~~SHALL~~shall be approved **PRIOR** to use; which ~~SHALL~~shall include tack welding and/or rework. Supplying product to BAE Systems with an unapproved, rejected, and/or incorrect WPS/BPS is a violation of the BAE Systems Purchasing Agreement and SQAM and ~~SHALL~~shall be considered non-conforming. The Supplier ~~SHALL~~shall be responsible for resubmitting the form ~~in the event that if~~ any changes in Base Material, Weld/Braze Procedure(s), the Part Number Configuration, and/or any other changes that impact the Welding/Brazing processes and/or procedures from the previously approved submittal. The form ~~SHALL~~shall be resubmitted if the BAE Systems Purchasing Order Part Number changes throughout configuration, regardless if all other variables have remained consistent from the previous approval.

Formatted: Font: Bold

NOTE: The processes and procedures that are to be used in fabrication SHALL directly align with the latest CDR008 approval on record. Should the Supplier resubmit and gain approval on the PO Part Number and Weldment/Brazement Part Number combination, any shall supersede all previous CDR008 approvals containing that specific combination are superseded by the most recent approval. Example: If the Supplier has a previously approved process (GMAW) and wishes to add an additional process (GTAW), both procedures and processes must be included in the resubmittal if they are intended to be used on the subject part.

Formatted: Font: Italic

Formatted: Font: Italic

Formatted: Font: Italic

Formatted: Font: Italic

Formatted: Font: Italic

Formatted: Font: Italic, Strikethrough

Formatted: Font: Italic, Strikethrough

Formatted: Font: Bold

The Supplier ~~SHALL~~shall be responsible for maintaining all supporting documentation including, but **NOT** limited, to the following: Procedure Qualifications, Performance Qualifications, Sub-Tier Supplier Certifications, Machine Calibration Documentation, and other applicable documentation required to demonstrate compliance in accordance with the requirements per the BAE Systems Purchasing Agreement. All documentation ~~SHALL~~shall be made available, as requested, to BAE Systems at all times.

Formatted: Don't add space between paragraphs of the same style

Note: For weld repairs and/or clarifications regarding weld/braze drawing requirements, the Supplier ~~SHALL~~shall submit a Vendor Information Request (VIR) Form (BMS 097908) for review and disposition **PRIOR** to use.

Formatted: Don't add space between paragraphs of the same style, Line spacing: single

008A Welding/Brazing-Procedures Requiring NAVSEA Approval

As a prerequisite, the Supplier ~~SHALL~~shall be responsible for satisfying all requirements in Sections 5.2.3 and 5.2.3.1 of S9074-AQ-GIB-010/248 REQUIREMENTS FOR WELDING AND BRAZING PROCEDURE AND PERFORMANCE QUALIFICATION ~~PRIOR to accepting POs with these requirements.~~

PRIOR to the start of fabrication, the Supplier ~~SHALL~~shall submit and gain approval for all procedure (s) per the PO Part Number.

The Supplier ~~SHALL~~shall be responsible for providing and/or qualifying Weld/Braze Procedure (s), in accordance with the specified code, **PRIOR** to fabrication.

The Supplier ~~SHALL~~shall submit the WPS/BPS (s) intended for part fabrication to BAE Systems Weld Engineering for review and approval via the CMS Supplier Weld/Braze Procedure Submission form (BMS 089136) **PRIOR** to the start of welding/brazing and fabrication. The latest version of the form ~~SHALL~~shall

Formatted: Font color: Black

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

be utilized and is accessible via the BAE Systems CMS Supplier Website. Each Weldment/Brazement part number and the applicable WPS/BPS (s) ~~SHALL~~shall be submitted individually.

The Supplier ~~SHALL~~shall submit the following documentation, at a minimum, as required per the applicable code and/or specification, **PRIOR** to the start of welding/brazing operations:

- **Welding Procedure Specification (WPS)/Brazing Procedure Specification (BPS)**
- Supporting **Procedure Qualification Record (PQR)/ Brazing Procedure Qualification Record (BPQR)**
- **Non-Destructive and Destructive Supporting Test Report**; tests ~~SHALL~~shall be performed in accordance with AWS B4.0 and NAVSEA T9074-AS-GIB-010-271 REV 1
- **Filler Material Certificate of Conformance (CoC)** for filler material utilized in the development of the applicable PQR
- **Procedure Approval Notice and/or artifact from NAVSEA and/or NAVSEA AR**, if the applicable PQR was previously reviewed and approved by NAVSEA
- For Special Welds and/or Special Processes, provide any **additional supporting documentation** that is required for submittal in accordance with the applicable drawing and/or specification

BAE Systems ~~SHALL~~shall be responsible for submitting the package to NAVSEA, for review and approval, as required.

Formatted: Font color: Black

All weld procedures and/or braze procedures to be utilized ~~SHALL~~shall be approved by BAE Systems **PRIOR** to use, which ~~SHALL~~shall include tack welding and/or rework. Supplying product to BAE Systems with an unapproved, rejected, and/or incorrect WPS/BPS is a violation of the BAE Systems Purchasing Agreement and SQAM and ~~SHALL~~shall be considered non-conforming.

Formatted: Don't add space between paragraphs of the same style

The Supplier ~~SHALL~~shall be responsible for resubmitting the form ~~in the event that~~if any changes in base material, weld/braze procedure(s), the part number configuration, and/or any other changes that impact the welding/brazing processes from the previously approved submittal. The form ~~SHALL~~shall be resubmitted if the BAE Systems PO part number changes throughout configuration, regardless of if all other variables have remained consistent from the previous approval.

Formatted: Don't add space between paragraphs of the same style

The Supplier ~~SHALL~~shall be responsible for maintaining all supporting documentation including, but **NOT** limited, to the following: procedure qualifications, performance qualifications, sub-tier ~~supplier~~Supplier certifications, machine calibration documentation, and other applicable documentation required to demonstrate compliance in accordance with the requirements per the BAE Systems Purchasing Agreement. All documentation ~~SHALL~~shall be made available, as requested, to BAE Systems at all times.

Formatted: Don't add space between paragraphs of the same style

Note: For weld repairs, clarifications, and/or deviations regarding weld/braze drawing and/or specification requirements, the Supplier ~~SHALL~~shall submit a Vendor Information Request (VIR) Form (BMS 097908) for review and disposition **PRIOR** to use.

Formatted: Don't add space between paragraphs of the same style, Line spacing: single

Formatted: Font: 12 pt, Font color: Black

009 Soldering

- The data shall be submitted and approved prior to shipment of the item in accordance with the data submission instructions located in the (SQAM) section 12 for this item. The Supplier shall submit soldering plans in accordance with the applicable specification requirements for this

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

item within (30) days of receipt of the Purchasing Agreement to the BAE Systems Authorized Purchasing Representative

- Procedures shall be submitted for all subcontracted soldering operations.
- BAE Systems reserves the right to disapprove the plan or to require changes in the plan, which it deems necessary to ensure the product conforms to IPC J-STD-001, Class 3 and Purchasing Agreement requirements
- A new Purchasing Agreement number with the same prime contract number as previously approved does not require extension of approval
- The plan shall include, as a minimum, detailed procedures to be followed and utilized throughout all areas of performance
- The Supplier must have approval from BAE Systems prior to beginning production. This approval will be in the form of a letter notifying you that your facility has satisfactorily completed a Soldering Audit. The approved program must be utilized in the performance of Purchasing Agreement
- Any and all records required by the approved program may be requested at any time and must be immediately available for review
- BAE Systems must approve changes to this program following previous approval (s)

010 Solderability

~~Material supplied, SHALL meet the solderability requirements of the product fabrication specification. When no solderability test is specified, the test SHALL be performed in accordance with MIL STD 202, Method 208.~~

~~Note: One hour steam aging is required for wire.~~

All soldered components shall meet the solderability requirements as defined in the purchase order agreement. In the event a purchase order does not define a solderability requirement the Supplier shall comply to Global Electronics Association (GEA)/Institute of Printed Circuits (IPC) Joint Industry-standard (J-STD-001, IPC-610, and IPC-620)). Any reference to an industry standard must be followed according to the latest revision.

The Supplier ~~SHALL~~shall provide a written certification stating that the components provided were tested and meet the applicable solderability requirements as stated above.

Formatted: Line spacing: single

011 Printed Wiring Boards (PWB)

The Supplier ~~SHALL~~shall provide for each shipment a written certificate stating that the boards were fabricated to the relevant specifications identified within the TDP. Test coupons and microsections must be maintained for a period of two (2) years and available for examination by BAE Systems.

Formatted: Line spacing: single

012 Flammability

A flammability certification to the specification noted on the drawing from the original material manufacturer or a flammability test report from a BAE Systems approved facility is required.

Formatted: Line spacing: single

Formatted: Line spacing: single

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

013 Nondestructive Examination Procedures

When the PO specifies nondestructive examination such as radiography, magnetic particle, liquid penetrant, or ultrasonic inspections, approval of the procedure is to be completed by or with oversight

© BAE Systems

BAE

from BAE Systems, level 3 personnel. The procedure ~~SHALL~~shall be submitted within thirty (30) days after receipt of the Purchasing Agreement.

All changes to the approved procedure ~~SHALL~~shall require re-submittal and approval. The revised procedure ~~SHALL~~shall not be implemented until written approval is received from BAE Systems.

Note procedure submittal to Combat Vehicle locations are ONLY required where Digital Radiography (DR), Computed Radiography (CR), or Phased Array Ultrasonic Testing (PAUT) techniques are utilized. Specs correlating to the above ASTM E2689=DR, ASTM E2033=CR, AWS D1.1, Annex H and Annex N=PAUT.

014 Nondestructive Examination ~~Inspection Report~~Certification

The Supplier ~~SHALL~~ furnish a certified test report stating that non-destructive examination (s) required per the TDP have been performed shall conduct NDT (i.e., Liquid Penetrant, Ultrasonic, Radiographic, Mag Particle, Visual Nondestructive Examination, and Eddy Current) in accordance with an approved test procedure as required the purchase order requirements and shall be conducted by the referenced level 2 or greater individual certified per TDP / specification and that requirements. Upon completion of NDT testing of the material is acceptable. The product, a certification ~~SHALL~~ also include, at a minimum, shall be provided to BAE Systems per the data submission instructions containing the following:

Formatted: Space After: 10 pt, Line spacing: single

- Type of test and coverage
- Applicable procedure specification (title, number and revision)
- Applicable acceptance criteria (title, number and revision)
- Actual data as defined in the applicable procedure specification
- Name and address of the company that ~~actually~~ performed the testing
- Certificate of process compliance
- Quantity of parts that were evaluated
- BAE ~~PQ~~Systems purchase order number-(s)

~~In addition to the above, data as required by the testing specification in the contract SHALL be included.~~

~~A test plan SHALL be developed detailing the non-destructive examinations parameters to be used in accordance with the applicable specification and SHALL be made available to BAE Systems upon request. Product NDT verification SHALL be completed by a certified individual required per the PO requirements, with a level II or higher certification.~~

- Technicians' name and Certification level of individual conducting NDT
- Radiograph deliverables shall include, at a minimum, the image of the part number, part serial number, identification of the area radiographed and identification of the view direction.

015 Control Tests

The Supplier ~~SHALL~~shall perform control tests at the frequency defined by the specification/QAP. The Supplier is responsible for determining the test schedule based on the production and delivery schedule per the Purchasing Agreement.

Note: If the TDP allows shipment prior to completion of the testing the ~~supplier~~Supplier must submit form "092245 Source Inspection Request / CDR Paperwork Submission" and form

Formatted: Line spacing: single

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

093504 "CDR 015 Part Submission Form Review Notification". Identification of projected date of test completion must be included in section B, section C will be approved by BAE Systems prior to shipping.

Following the completion of testing a test report ~~SHALL~~shall be submitted and approved with form "092245 Source Inspection Request/CDR Paperwork Submission" and form 093504 "CDR 015 Part Submission Form Review Notification".

~~Suppliers are required to inform BAE Systems using VIR form 089725 when any of the following situations occur. A change in the planned test schedule that may impact delivery, a failure through test equipment or a failure with product itself prior to continuance of testing.~~

Formatted: Font: 11 pt

Formatted: Line spacing: single, Adjust space between Latin and Asian text, Adjust space between Asian text and

Formatted: Font: Not Italic

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Forms are available on the Supplier website.

Formatted: Line spacing: single

MIL-HDBK-831 should be used as a guide in developing the test report format. As a minimum, the test report ~~SHALL~~shall include:

- BAE Systems part number
- All applicable BAE Systems Purchasing Agreement numbers
- Prime Contract number (this is specified on the Purchasing Agreement)
- Applicable drawings/specification and revision level
- Type of test (i.e., Group "C," Group "D," etc.)
- Tests performed and results
- Test completion date
- Next test date/submittal
- Applicable serial numbers that were tested
- Sample size
- Sample identification, (if applicable)
- Production interval (or Purchasing Agreement line number)
- Printed name, signature, and title of Supplier's representative
- Report date
- Any additional data or information required to show full compliance to the control test requirements

Formatted: Font: 11 pt

Suppliers are required to inform BAE Systems using VIR form 089725 when any of the following situations occur. A change in the planned test schedule that may impact delivery, a failure through test equipment or a failure with product itself prior to continuance of testing. Forms are available on the Supplier Website.

Formatted: Line spacing: single, Adjust space between Latin and Asian text, Adjust space between Asian text and

Formatted: Font: Not Italic

016 Plating

The Supplier ~~SHALL~~shall provide a written certification proving the plating was performed in accordance with all Purchasing Agreement, drawing, and specification requirements prior to shipment of the product. The facility performing the plating ~~SHALL~~shall prepare the certification.

Formatted: Line spacing: single

The Certification **MUST** include, as a minimum:

- Part number and revision
- BAE Systems Purchasing Agreement number
- Plating process specification and revision used
- Complete lot traceability to all certifications related to the BAE Systems Purchasing Agreement
- Printed name, signature, and title of the Supplier's representative
- Report date
- Physical and Chemical Material Certs for material or parts provided by Supplier

Formatted: Line spacing: single

Pretreatment on steel parts with a tensile strength of 1000 MPa (31 HRC) or greater that contain tensile stresses caused by cold forming or cold straightening which have not been heat treated after the cold forming process, ~~SHALL~~shall be heat treated for stress relief to reduce the risk of hydrogen embrittlement in the part before the cleaning and electroplating processes. Heat treatment times and

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

temperatures ~~SHALL~~shall be in accordance with Table 1 of ASTM B849 for steel, based on its tensile strength.

The following requirements apply when zinc plating per ASTM B633 is specified:

Formatted: Line spacing: single

- Post ~~Coating Treatments~~coating treatments of ~~Iron~~iron and ~~Steel~~steel for the ~~Purpose~~purpose of ~~Reducing~~reducing the ~~Risk~~risk of ~~Hydrogen Embrittlement~~hydrogen embrittlement (Baking)
- Electroplated steel parts having a tensile strength greater than 1200 MPa (39 HRC) as well as surface hardened parts, ~~SHALL~~shall be baked to reduce the risk of hydrogen embrittlement.
- Baking of electroplated steel parts with tensile strength 1200 MPa (39 HRC) or less is not mandatory.
- Steel parts having a tensile strength greater than 1200 MPa (39 HRC) as well as surface hardened parts, ~~SHALL~~shall be baked to reduce the risk of hydrogen embrittlement. (For such parts, when the purchaser did not specify the bake requirements in the ordering information, bake times and temperatures ~~SHALL~~shall be in accordance with the appropriate ER Class in Guide ASTM B850 Table 1).

The certification for baking ~~SHALL~~shall also include:

- Baking temperature; requirement and actual
- Baking time; requirement and actual
- A statement that the baking operation for hydrogen embrittlement relief was started within 3 hours of plating completion or as required per the specification.

017 Paint Certification

The Supplier ~~SHALL~~shall provide a copy of the written certification documenting that painting was performed in accordance with all Purchasing Agreements, drawing, and specification requirements prior to product shipment.

Formatted: Line spacing: single

The facility performing the painting ~~SHALL~~shall prepare the certification, which ~~SHALL~~shall include:

- Name and address of the finisher
- Part number and revision
- BAE Systems Purchasing Agreement number
- List of specifications and their revisions used in the processing of the paint
- Dry film paint thickness of a sample of actual parts for the primer and ~~top coat~~topcoat
- Salt spray evidence as required per specification
- ~~Date in which the last salt spray test was performed for this process (within last 60 days)~~
- Adhesion testing ~~evidence~~results as required per specification
- ~~Surface blast profile~~
- Material lot/batch number (s)
- Material expiration date (s)
- Printed name, signature, and title of Supplier's representative
- Certification date

All test and inspection documentation ~~SHALL~~shall be available for BAE Systems' review upon request.

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt
Formatted: Font: 10 pt

Items requiring painting in accordance with MIL-STD-1303 ~~SHALL~~shall instead be painted in accordance with NAVSEA Drawing 7250920 as required by any associated paint photographs.

018 Physical and Chemical Test Reports

The Supplier ~~SHALL~~shall provide the ~~raw material certification including all actual~~chemical, mechanical, and physical ~~test/testing~~ results ~~required as~~ by the ~~TDP~~purchase order for ~~the each~~ material or ~~material used in the~~ finished product ~~shipped under this Purchasing Agreement~~for each shipment. ~~These results shall be in accordance with traceability~~the purchase order requirements. Material shall ~~comply to any applicable DFARS such as Specialty Metals~~. These requirements shall be flowed down to any sub-tier Suppliers.

Material certification shall be legible and include:

- Purchase order number
- Traceability from the Supplier to the original mill/manufacturer, ~~heat~~
- ~~Heat lot, and~~
- ~~Include country of origin. For material subject to the SQAM paragraph 6.6 Traceability of Specialty Metals, evidence of compliance SHALL be included. Certificate is required to state affirmation/compliance to DFARS 252.225-7009. Material certifications supporting components within an assembly SHALL be labeled with the component~~
- Original manufacturer part number if available
- BAE Systems part number for material if applicable
- Original manufacturer name
- Certification Statement
- Authorized signature ~~or identifier it correlates to~~ quality stamp with the title(s) of the Seller's personnel who have signed or stamped the certificate

Formatted: Font: 11 pt
Formatted: Font: 11 pt
Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: Font: 11 pt

019A Test Samples – Tensile Testing

The Supplier ~~SHALL~~shall provide a set of two samples (un-machined test bars/sheet stock) suitable for the mechanical testing as required by Purchasing Agreement or referenced specification. Both ~~SHALL~~shall be made from the same melt and heat treated in the same lot as the supplied parts. ~~Samples shall not be etched or stamped in any manner and shall be individually packaged with labeling. Labeling shall include PO number, material heat number and the respective chemical and physical certs for the sample shall be included in the box.~~ Contact Purchasing Representative for sample delivery location requirements if unspecified.

Formatted: Line spacing: single

019B Material/Process ~~Samples~~Sample

A representative material test sample (the same as the material lot) is required. The test sample ~~SHALL~~shall be processed simultaneously with the material it represents, through all special processing. The sample ~~SHALL~~shall be of sufficient size and configuration ~~to permit BAE Systems will determine the with the same~~ heat treatment, plating, painting, etc., ~~results in lieu of destroying as~~ a completed part. ~~Sample shall not be etched or stamped in any manner and shall be individually packaged with labeling. Labeling shall include PO number, material heat number and the respective chemical and physical certs for the sample shall be included in the box.~~ The ~~supplier~~SHALLSupplier shall submit the processed test sample with completed material/parts to BAE Systems. Contact Purchasing Representative for sample delivery location requirements if unspecified.

BAE Systems.

Formatted: Line spacing: single, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers

Formatted: Font: Arial, 10 pt
Formatted: Font: Arial, 10 pt
Formatted: Font: Arial, 10 pt
Formatted: Font: Arial, Italic
Formatted: Normal, Left

020 A-G Heat Treating

The Supplier shall provide a written certification proving the heat treat was performed in accordance with all Purchasing Agreement, drawing, and specification requirements prior to shipment of the product. Where multiple components require heat treat the certification shall differentiate between each part or individual certifications per part shall be provided. The facility performing the heat treat shall prepare the certification.

The Certification **MUST** include, as a minimum:

- Part number and revision
- BAE Systems Purchasing Agreement number
- Heat treat process specification and revision used
- Complete lot traceability to all certifications related to the BAE Systems Purchasing agreement. The Supplier SHALL
- Heat treat time at temp and temperature.
- Hardness results
- Printed name, signature, and title of the Supplier's representative
- Report date

The Supplier shall conduct a visual inspection for cracks or other injurious defects with qualified personnel as required per the contract.

~~When the drawing specifies a hardness range for materials due to quench and temper or other practices, actual results SHALL be recorded on the certification.~~

~~When heat treating is performed by a facility other than the Supplier shown on the Purchasing Agreement, the name of that subcontractor and a copy of the certificate furnished by the subcontractor for the heat treatment SHALL be furnished to BAE Systems.~~

~~When specified on the drawing and/or the Purchasing Agreement, test samples SHALL be provided to BAE Systems for evaluation.~~

~~The below processes SHALL be completed as stated per specific drawing requirements. When a conflict is noted between this document and specific drawing requirements, the drawing requirements take precedence.~~

020A Visual Metallographic Inspection

~~Visual inspection at a magnification of 5X SHALL be performed on heat treated items. Cracks, seams, laps or other injurious defects SHALL not be allowed. For steel carburized parts, the heat treat condition prior to carburizing SHALL be either quench and tempered or normalized and tempered. The heat treat process and atmosphere control SHALL be such that no decarburization occurs on the surface as detectible by metallographic sectioning under magnification at 100X, method specified on the drawing or appropriate specification. Exceptions are stress proof, fatigue proof, precipitation hardening grades of steel, margining steels and structural steel such as HY , HY 100, Cor ten, etc. This will minimize distortion and ensure that proper hardness is achieved.~~

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Font: +Headings (Cambria), 12 pt, Font color: Accent 1

Formatted: Font: 11 pt

Formatted: Font: Calibri

Formatted: Indent: Left: 0.5", Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

020B Quench and Temper (Core Hardness Specified)

A test specimen (or additional part) of the same alloy and same size, within 20% of the largest cross section thickness, SHALL be heat treated with each heat treat lot. The test sample SHALL have a length at least one inch longer than the section thickness or two times the diameter. The specimen or sample part SHALL be cross sectioned at mid-length of the largest cross section thickness plus or minus 3/8 inch. The Supplier SHALL submit a report including the actual surface hardness and core hardness at 1/4 radius (core hardness measured on cut surface).

020C Quench and Temper (Surface Hardness Specified, Core Hardness Not Specified)

The report SHALL include a statement of the surface hardness findings for each heat treat lot. Testing SHALL be done in areas identified on the drawing or in such a manner as to not damage the critical surface finish as defined by the drawing.

A test specimen (or additional part) of the same alloy and same size, within 20% of the largest cross section thickness, SHALL be heat treated with each heat treat lot. The test sample SHALL have a length at least one inch longer than the section thickness or two times the diameter. The specimen or sample part SHALL be cross sectioned at mid-length of the largest cross section thickness plus or minus 3/8 inch. The Supplier SHALL submit a report including the actual surface hardness and core hardness at 1/4 radius (core hardness measured on cut surface).

020D Case Hardening – Carburizing

A test specimen of the same alloy and similar configuration as the part SHALL be processed with each heat treat lot to verify case depth, surface and core hardness requirements, and microstructure. The Supplier SHALL submit a report with the required case depth hardness actual results obtained and microstructure per specified standard. Certification SHALL be submitted with each heat treat lot.

020E Case Hardening – Nitriding

A test specimen of the same alloy, same hardness, and similar configuration as the part SHALL be processed with each heat treat lot to verify case depth, hardness requirements, and to monitor thickness of white layer. The Supplier SHALL submit a report with required case depth, hardness, process temperature, and actual results obtained. Certification SHALL be submitted with each heat treat lot.

020F Surface Hardening – Flame or Induction

The Supplier SHALL provide certification with each lot reporting the actual case depth, surface and core hardness values obtained. First Article proof tests with pattern, equipment power setting, quench media, and other critical process parameters SHALL be maintained by vendor.

020G Stress Relief

Certification for stress relief SHALL report the actual processing time, temperature, and number of cycles for each lot as defined in the drawing or specification.

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

021A Mercury Exclusion

The Supplier SHALL certify that the material shipped All supplies furnished under this Purchasing Agreement ~~does purchase order shall not be contaminated by mercury or mercury compounds, nor shall they contain functional mercury in any form and that no mercury-bearing instruments and/or equipment that might cause contamination, have been.~~ If mercury is used in the ~~manufacture~~ processing, fabrication, testing or assembly, or testing of any the supplied material, the Supplier shall take responsible steps to ensure that the item(s) are not contaminated. Each shipment of material shipped under this Purchasing Agreement. This requirement must be included in all sub-tier POs ~~however, shall include certification is only required from the~~ of conformance to the above requirement. The certification shall reference purchase order number, part number, description and quantity shipped. Any item (s) provided that do contain mercury must have BAE Systems tier1 suppliers ~~when requested approval in writing prior to delivery and protected from damage during shipment.~~

Formatted: Line spacing: single

021B Lead

The Supplier ~~SHALL~~ shall certify that the material shipped under this Purchasing Agreement does not contain lead in any form and that no lead-bearing instruments and/or equipment that might cause contamination, have been used in its manufacture, fabrication, assembly, or testing of any material shipped under this Purchasing Agreement. This requirement must be included in all sub-tier purchase orders; however, certification is only required from the BAE Systems Tier 1 ~~suppliers~~ Suppliers.

Formatted: Line spacing: single

022 Material Traceability

~~All finished product lots must be traceable to raw material heat/lots, and the Supplier must maintain material traceability throughout all steps of the manufacturing process including any outside processing.~~ The Supplier shall submit with each shipment a certificate of traceability that identifies the source of origin for this item or items held within this assembly for each batch / lot provided through every stage of its manufacturing evolution. When multiple batches / lots are provided for a given item or assembly a separate certificate of traceability document (s) shall be delivered where applicable to clearly define traceability of this item or items held within this assembly. Multiple batches / lots shall be separated and or clearly identified and or traceable through the delivered certificate of traceability to maintain distinction of all items included to the Original Equipment / Original Component manufacturer (OEM/OCM). Traceability data shall include the specific manufacturer, specific manufacturer's batch identification for the item(s) such as date codes, lot codes, serializations, or other batch identifications for each stage of the item (s) manufacturing. Packaging shall be marked with the purchase order part number, direct Supplier name as listed on the purchase order, QTY and any date codes, lot codes, serializations, or other batch identifications required to discern the delivery. Modification or altering an item including marking is prohibited unless directed by the TDP or purchase order.

Formatted: Line spacing: single

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

022A Material Traceability – Weapon Systems – VPM Tubes

For Legacy Weapon Systems, VPM program, the following requirements apply:

- Supplier ~~SHALL~~ shall comply with all provisions of sow EB5638 and EB6075.
- Material verification ~~SHALL~~ shall be accomplished upon receipt and prior to delivery.
- Photographic evidence of product condition as received and as shipped MUST be provided.
- Inspection/ Objective Quality Evidence (OQE Reports SHALL) reports shall include the Unique Identification Number (UIN) from the provided raw material and a unique serial number that SHALL also be marked on the part to match the inspection records.

- Part markings should include a minimum of the following:
 - MFR name (Symbol) and cage code, material traceability serial number and heat number (EB Unique Number – Mill ~~SN~~Serial Number for plate
 - EB/OEM ~~SN~~Serial Number for forgings/castings, lot number (Bar), Material Identification Control (MIC-NO) number (CU-NI, AL-BZ PLATE, BAR STOCK),
 - Material Specification (EX) HY-80, DELRIN-150, FORGING/PLATE SPEC),
 - Material Inspection Markings (VT, MT, RT, UT), EB Drawing ~~NO~~Number- Item ~~NO~~Number/Revision from the BAE Systems provided-discrete ~~dwg~~drawing numbers page, BAE Systems material tracking number provided on raw material.

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Font: 11 pt

022B Material Traceability – Weapon Systems – Submarine Box Parts

For Legacy Weapon Systems, submarine programs, the following requirements apply:

- ~~Supplier SHALL~~The supplier shall comply with all provisions of sow EB5638, EB2678, EB5612 and EB6075.
- ~~Material verification SHALL~~shall be accomplished upon receipt and prior to delivery.
- ~~Photographic evidence of product condition as received and as shipped MUST be provided.~~
- ~~Prior to delivery, a completed workbook, submarine box parts, CDR 022B; quality requirement matrix must be submitted as per below:~~
 - MFR name (Symbol) and cage code, material traceability serial number and heat number (EB Unique Number – Mill SN for plate
 - EB/OEM ~~SN~~Serial Number for forgings/castings, lot number (Bar), MIC NO (CU-NI, AL-BZ PLATE, BAR STOCK)
 - Material specification (EX) HY-80, DELRIN-150, FORGING/PLATE SPEC)
 - Material inspection markings (VT, MT, RT, UT), EB ~~dwg~~ drawing number- item ~~nonumber~~/revision from the BAE Systems provided - discrete ~~dwg~~drawing numbers page BAE Systems material tracking number provided on raw material.

Formatted: Line spacing: single

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: Font: 11 pt, Not Bold

Formatted: Font: 11 pt

023 Age Control

Age sensitive items include, but are not limited to, paint, adhesives, and rubber products. The following requirements apply to all items with this requirement:

- Age sensitive items SHALL be delivered as directed by the requirement assigned below:

023A with 023A 75% Shelf Life / Limited Life Material (LLM)

Material provided under this purchase order has been identified as shelf life / Limited Life Material (LLM) applicable.

The Supplier shall provide material properly marked and protected from environmental conditions during shipment. Marking shall be on the lowest level packages containing the material. Marking shall also be applied to exterior packaging that inhibits visibility of lower-level package marking. Marking to include:

- Date of cure or manufacture.
- Expiration date at minimum of 50% of the shelf life remaining to include month / year. (see note 1)
- 023B withMarking shall be permanent and not affect form, fit or function
- Environmental control provisions shall be identified on packaging.
- Material shall be stored, protected, and shipped per said provisions.

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

- Low temperature / frozen materials shall be monitored during storage and shipping processes, evidence of controls shall be provided upon delivery.
- Unless otherwise stipulated by the purchase order product received at BAE Systems shall have a minimum of 75% of the shelf life remaining. (see note 1)

Note: The expiration date and shelf life shall be that as defined by the manufacturer unless BAE Systems shelf life is stipulated through purchase order.

023B 50% Shelf Life / Limited Life Material (LLM)

Material provided under this purchase order has been identified as shelf life / Limited Life Material (LLM) applicable.

The Supplier shall provide material properly marked and protected from environmental conditions during shipment. Marking shall be on the lowest level packages containing the material. Marking shall also be applied to exterior packaging that inhibits visibility of lower-level package marking. Marking to include:

- Date of cure or manufacture.
- Expiration date at minimum to include month / year. (see note 1)
- Marking shall be permanent and not affect form, fit or function
- Environmental control provisions shall be identified on packaging.
- Material shall be stored, protected, and shipped per said provisions.
- Low temperature / frozen materials shall be monitored during storage and shipping processes, evidence of controls shall be provided upon delivery.
- Unless otherwise stipulated by the purchase order product received at BAE Systems shall have a minimum of 50% shelf life remaining. See note 1:

023C with a minimum of 85% of the

- Note: The expiration date and shelf life remaining.
- 023D others shall be that as directed defined by contract.

- All age sensitive items and their respective shipping containers SHALL be permanently marked with the cure/manufacture and expiration dates in addition to any other required markings.
- For parts delivered on a spool or reel, the marking must be applied to a visible location on the outside of the spool or reel.
- The cure/manufacture and expiration dates SHALL be in either Quarter/Year format (for product with a shelf life in excess of three (3) years) or Month/Year format (for product with a shelf life of three (3) years or less). The method of marking and the marking height SHALL be in the manufacturer's format; however, the marking SHALL not affect the part's form, fit, or function.

Example: CURE 4Q/2010

EXP 4Q/2016

- In addition to the requirements of SQAM paragraph 8.5, when a CoC for age sensitive items is required, it SHALL include: stipulated through purchase order.

- a) Lot traceability by run, batch, lot, or date of manufacture
- b) Shelf life expiration date (as required by specification)
- c) Storage conditions to achieve shelf life, if not stated on the material package

Formatted: Font: Arial

Formatted: Body Text, Indent: Left: 0.29", Right: 0.43", Line spacing: single, Tab stops: Not at 2.81"

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

024 Non-manufactured Coniferous Wood Products

All wooden pallets and wood containers produced entirely or in part of non-manufactured softwood, species ~~SHALL~~shall be constructed from heat-treated coniferous material. This material must be certified accordingly by an accredited agency recognized by the American Lumber Standards Committee (ALSC) in accordance with the Non-manufactured Wood Packaging Policy and Non-manufactured Wood Packaging Enforcement Regulations. The Supplier ~~SHALL~~shall maintain on file at their facility, and provide upon request to BAE Systems, a CoC from the accredited heat treat facility.

Formatted: Line spacing: single

025 Special Packaging

Material is to be packaged in accordance with the packaging instructions provided in the body of, or attached to this Purchasing Agreement. A statement that the packaging is in accordance with the specified requirements will be included in the CoC (reference SQAM ~~paragraph 8.5).~~ section 12).

Formatted: Line spacing: single

026 Quality Requirements

The Supplier ~~SHALL~~shall maintain on file, and provide to BAE Systems upon request, objective quality evidence demonstrating compliance to all ~~of~~the requirements of the Purchasing Agreement. When BAE Systems requests documentation, the documentation ~~SHALL~~shall be provided in a commonly readable electronic format.

Formatted: Line spacing: single

027 Goods / Services Certificate of ~~Compliance~~Conformance

~~The Supplier SHALL provide an electronic copy of their CoC for each shipment as defined by paragraph 8.5 of the SQAM.~~

The Supplier shall generate and provide a CoC with each shipment. The instructions for submitting the CoC shall be as defined by purchase order. The CoC shall provide a statement of conformity (e.g., "I hereby certify the materials/service supplied was produced and or provided in accordance with the full requirements of the purchase order.) and Signature and title of authorized Supplier representative with date. The paperwork for each shipment shall contain as applicable the following information:

- Supplier's name and address
- Manufacturer's name and address (if different from Supplier name above)
- BAE Systems purchase order number and line number
- BAE Systems item number, description, and revision as specified on the purchase order (excluding BAE Systems revision for COTS items)
- Manufacturer's item number and revision if identified in the BAE Systems purchase order
- Unique Item Identifier (e.g., date codes, lot codes, heat codes, serializations, unique item identifiers, or batch identifications (as applicable)
- Total Quantity and Quantity per lot (as applicable)
- Exceptions, including waivers and deviations (as applicable)
- Signature, printed name, and title of signer (electronic or digital signatures are acceptable)
- Date of shipment

By providing this COC the Supplier confirms the product meets the following: Item (s) / service meets all the requirements of the purchase order and its TDP at the prescribed revision level. The product is provided in a new, non-salvaged and unaltered condition per the TDP and or purchase order. Note this typically assimilates but is not limited to new or unaltered circuit cards or electronic components.

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Note: Pre-submittal and approval is not required for material delivered to Weapon Systems locations.

028 Unique Identification (UID)

This item requires UID marking in accordance with Mil-Std-130/TDP requirements. Verification and validation must be performed in accordance with MIL-STD-130. Verification and validation reports in accordance with DI-MGMT-81804 must be kept on file. If the UID marking is already present, verify and validate in accordance with MIL-STD-130. If the scan fails, replace the existing marking with new UID marking. SQAM required marking ~~SHALL~~shall be rubber stamped in a location close to the UID plate including the Supplier's CAGE code if not part of UID plate information.

Formatted: Line spacing: single

029 Serialization

The Supplier ~~SHALL identify~~shall implement a serialization system, which includes assigning unique, permanent, and individual serial numbers to all items ~~using marking shipped under this purchase order.~~

The serial numbers shall be affixed to the items in accordance with the methods as required by specified in the purchase order, drawings, or specifications, and/or the PO. Serialization logs SHALL be maintained. Where BAE Systems elects to supply these numbers, they will be provided through the purchase order.

The Supplier shall maintain a serialization log to prevent duplication of serial numbers. The Supplier's quality system SHALL and ensure traceability of that all serialized items and materials are traceable to the original materials.

The Supplier shall include serialization documentation with each shipment. When two or more serialized parts are joined in an assembly, the Supplier ~~SHALL~~shall include a list ~~for with~~ each assembly serial number ~~with the, including~~ part numbers, change letters, and component serial numbers ~~making up the assembly serial number. This information SHALL be supplied with each shipment.~~

Formatted: Space After: 10 pt, Line spacing: single, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Note: Weapon Systems VPM program - The Supplier ~~SHALL~~shall comply with the above provisions and the entirety of EB5638.

Formatted: Line spacing: single

030A Phoenix Approved Special Processors (BAE Systems)

The Supplier must use BAE Systems' approved sources for special processes such as thermal processing, metal finishing, metal joining, non-destructive testing, etc. A current approved processor listing may be obtained from the respective BAE Systems Buyer.

Formatted: Line spacing: single

030B Phoenix Approved Special Processors (Customer)

The Supplier must use BAE Systems' customer approved sources for special processes such as thermal processing, metal finishing, metal joining, non-destructive testing, etc. A current approved processor listing may be obtained from the respective BAE Systems Buyer.

Formatted: Line spacing: single

030C NADCAP Approved Special Processes

All special processes identified herein and utilized on a BAE Systems PO/subcontract require certification by NADCAP. NADCAP Certification will be required for heat treating, painting/coating (non-CARC) and plating. These special process requirements identified herein ~~SHALL~~shall be flowed down to all sub-tier

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

© BAE Systems

BAE

Page Page 41 of 69

© BAE SYSTEMS, INC. All Rights Reserved

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Suppliers as applicable. The Supplier ~~SHALL~~shall provide a current CoC certifying compliance for the special process identified and performed as required by the TDP. All special process ~~suppliers~~Suppliers or their sub-tier ~~suppliers~~Suppliers utilized on the PO/subcontract ~~SHALL~~shall have a current accreditation by NADCAP. The CoC ~~SHALL~~shall define and document each process used in satisfying the TDP/Subcontract requirements and the date of the last audit. Special processes will be as defined in our SQAM, AS9100 and by NADCAP. All costs associated with NADCAP accreditation ~~SHALL~~shall be borne by the special processor.

030D Combat Vehicles Approved Special Processors (BAE Systems)

The Supplier is to use BAE Systems' approved sources for special processes such as thermal processing, metal finishing, metal joining, non-destructive testing, etc. A current approved processor listing may be obtained from the respective BAE Systems Buyer.

Formatted: Line spacing: single

030E High Strength Fasteners (HSF) for Naval Products "Zinc"

The following is a Legacy Weapons Systems requirement for all High Strength Fasteners:

Formatted: Line spacing: single

This item is a high-strength fastener. All High-Strength Fasteners (HSF) of this type must meet the following requirements: (Failure to meet these requirements will result in rejection, without exception)

*****NOTE: ALL OF THE LISTED CDR REQUIREMENTS MUST BE APPROVED PRIOR TO DELIVERY. NO EXCEPTIONS. ANY DELIVERY WITHOUT APPROVAL WILL BE REJECTED AND RETURNED TO SUPPLIER*****

HIGH STRENGTH FASTENER SPECIAL REQUIREMENTS

Currently, HSF can only be zinc or zinc/nickel plated to (96-11402, only when the drawing states this requirement) and must be plated at Nico Plating (Minneapolis, MN) and purchased from E & A Products.

All other HSF: The following applies:

- Procurement of all HSF must be through:

E & A PRODUCTS CO INC
11885 Brockton Lane
MAPLE GROVE, MN 55369

- Plating for all HSF must be completed by:

NICO PRODUCTS
2929 1ST AVENUE SOUTH
MINNEAPOLIS, MN 55408
(PH) 612-822-2185

When placing orders with Nico Products, the PO to Nico Products must state that these are for BAE Systems, Weapons Systems, and that these instructions must be flowed down to Nico Products.

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

@ BAE Systems

BAE

Page-Page 42 of 69

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Supplier Quality Assurance (SQA) provisions per the BAE Systems SQAM must be adhered to. (All specifications referenced SHALLshall be compliant to the latest revision).

The delivered documentation package SHALLshall contain the following:

Formatted: Line spacing: single

- A CoC confirming that the part was manufactured to the requirements of FF-S-86 or related ASTM B18 specification and ANSI/ASME B18.3 for dimensional compliance.
- A chemical and physical certification, (material must be melted in the USA or a qualifying country per DFARs requirements, an actual mill certification with the country of origin listed is required).
- The oven charts required for hydrogen embrittlement pre and post plate baking operation, after plating from the plater.
- NDT test certification after heat treating required, prior to plating.
- A document that states the parts are mercury free when completed.
- All certifications traceable to the appropriate BAE Systems PO, on each required document.
- The special plating restrictions are as follows (certification is required to document compliance as listed):
 1. No cathodic or acid cleaning allowed.
 2. The minimum workable current density SHALLshall be used in the zinc bath. Cyanide zinc and other low efficiency baths SHALLshall **NOT** be used.
 - 2.1 Practice of zinc activation, post hydrogen embrittlement, bake relief, by immersion in zinc plating bath with electric current is prohibited. Only weak acid per ASTM B6333 is allowed.
 3. Hydrogen embrittlement bake @ 400 +/-25 deg F for 24 hours within 3 hours.
 4. Plating thickness, adhesion, corrosion resistance, hydrogen embrittlement relief and workmanship SHALLshall be verified IAW ASTM B 633.
- A metallurgical NDT inspection per ASTM E 1444, after stress durability testing of samples parts used for testing. (Magnetic Particle (MP) inspection).
- A stress durability test, per AIA/NAS NASM-1312-5, 200 hours, 80% of the rated minimum tensile strength (ref ASTM A574 or ASTM A574M) sample size IAW SHALLshall be completed after plating, **(a minimum of 5 parts must be tested)**.
- The locking patch (when required) SHALLshall be per MIL-DTL-18240, except prevailing and breakaway torques per IFI-124 (when required by DWG).
- A First Production Inspection (FPI) in accordance with the CDR Manual is required. After the first piece and provided this item has been in continuous production for the last 24 months, an in-process inspection must be completed and submitted for our review to demonstrate compliance. This requirement applies throughout the remainder of the 24-month period, following the initial first article inspection.
- All items must be completed per the requirements ~~and submitted for source inspection.~~ The Supplier must receive written BAE Systems permission to ship. A copy of the permission SHALLshall be included with all items being shipped.
 5. A pre-approved plating rework procedure is required and must be approved by BAE Systems, for all parts. Rework must be identified using a punch mark, (x), located on the head of the fasteners.
 6. BAE SYSTEMS, WEAPONS SYSTEMS DIVISION, must approve the "Plating Process Control Procedure" prior to plating HSF. Written evidence of approval is required to be available upon demand.

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt
Formatted: Font: 10 pt

7. Any detail that is not documented as described, herein, is cause for rejection, return, and replacement as needed. It is the responsibility of the Supplier to review for compliance, all items prior to submittal. There are no allowable exceptions to HSF. All items must be provided and comply as noted. All rejections are at the cost to the Supplier, with provided conforming items.

030F High Strength Fasteners (HSF) for Naval Products “Cadmium”

The following is a Legacy Weapons Systems requirement for all High Strength Fasteners:

Scope: Fasteners that require only Cadmium plating per NAS672, or SAE-AMS-QQ-P-416 as listed on the drawing, must be plated per the drawing requirements without exception. This item is a high-strength fastener. All High-Strength Fasteners (HSF) of this type must meet the following requirements: (Failure to meet these requirements will result in rejection, without exception)

******NOTE: ALL OF THE LISTED CDR REQUIREMENTS MUST BE APPROVED PRIOR TO DELIVERY. NO EXCEPTIONS. ANY DELIVERY WITHOUT APPROVAL WILL BE REJECTED AND RETURNED TO SUPPLIER******

HIGH STRENGTH FASTENER SPECIAL REQUIREMENTS

Currently, HSF can only be Cadmium plated when the drawing states this requirement and must be plated at a supplier capable of meeting the Cadmium plating requirements per the specific drawing and as listed below:

Per NAS672:
This specification outlines the procedures to be followed in the cadmium plating of fasteners and fittings fabricated of non-corrosion resistant steel in the heat treat ranges of 180 ksi and higher and is designated to produce parts in which hydrogen embrittlement is minimized.

Per QQ-P-416 (Superseded by SAE-AMS-QQ-P-416):
See section 3.2 in its entirety, for defined requirements, applied as applicable.

Supplier Quality Assurance (SQA) provisions per the BAE Systems SQAM must be adhered to. (All specifications referenced shall be compliant with the latest revision). A VIR must be submitted notifying BAE Systems that this will be Cadmium plated parts that need BAE Systems approval.

The delivered documentation package shall contain the following:

- A CoC confirming that the part was manufactured to the requirements of the specific drawing.
- A chemical and physical certification, (material must be melted in the USA or a qualifying country per DFARs requirements, an actual mill certification with the country of origin listed is required).
- The oven charts required for hydrogen embrittlement pre and post plate baking operation, after plating from the plater.
- NDT test certification after heat treating required, prior to plating.

Formatted: Font: Arial, 10 pt
Formatted: Font: Arial, 10 pt
Formatted: Font: Arial, 10 pt
Formatted: Font: Arial, Italic
Formatted: Normal, Left

- A document that states the parts are mercury free when completed.
 - All certifications traceable to the appropriate BAE Systems PO, on each required document.
 - The special plating must meet the requirements of the Cadmium plating specification NAS 672 or QQ-P-416 (Superseded by SAE-AMS-QQ-P-416).
 - A metallurgical NDT inspection per ASTM E 1444, after stress durability testing of samples parts used for testing. (Magnetic Particle (MP) inspection).
 - A stress durability test, per AIA/NAS NASM-1312-5, 200 hours, 80% of the rated minimum tensile strength (ref ASTM A574 or ASTM A574M) sample size IAW shall be completed after plating. (a minimum of 5 parts must be tested). NOTE: Testing must be completed after plating and finishing operations.
 - The locking patch (when required) shall be per listed specification.
 - A First Production Inspection (FPI) in accordance with the CDR Manual is required. After the first piece inspection is approved by BAE Systems and provided this item has been in continuous production for the last 24 months, an in-process inspection must be completed and submitted for our review to demonstrate compliance.
 - All items must be completed per the drawing requirements. The Supplier must receive written BAE Systems permission to ship, after submittal and approval of the data package. A copy of the permission shall be included with all items being shipped.
8. Any detail that is not documented as described, herein, is cause for rejection, return, and replacement as needed. It is the responsibility of the Supplier to review for compliance, all items prior to submittal. There are no allowable exceptions to this CDR-Q30F requirements. All items must be provided and comply as noted. All rejections are at the cost to the Supplier, with provided conforming items.

032 Ballistic Requirements-Transparent Armor

A ballistic FAT ~~SHALL~~shall be performed and accepted prior to any production of transparent armor. All drawing and specification requirements ~~SHALL~~shall be met as required for the ballistic FAT and ballistic lot testing.

Formatted: Line spacing: single

The ballistic sample submission process for York purchased material is tested at BAE Systems, San Jose:

- The Supplier ~~SHALL~~shall request BAE Systems source inspection prior to shipping the samples for ballistic testing, with the following requirements:
 - The Supplier ~~SHALL~~shall submit Form 092245 Source Inspection Request/Approval form as required by CDR005 per the data submission instructions on form 092245.
 - Forms are available on the Supplier website listed in the PO text.
- During source inspection, the Supplier and BAE Systems CMS source inspector ~~SHALL~~shall complete form 091889 Ballistic Test Submittal form.
 - The source inspector ~~SHALL~~shall determine if the contract requires DCMA witness of the ballistic test.
 - The source inspector ~~SHALL~~shall enter the project and task numbers on the submittal form (when applicable).
- Signed copies of the source inspection approval and the ballistic test forms ~~SHALL~~shall be included with the shipping documents for the test sample.

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

- In addition to the marking requirements, specified in the PO and on the drawings, ALL test specimens, shipping containers and associated documents ~~SHALL~~shall be clearly marked "First Article Sample" or "Lot Sample."
- Following ballistic first article approval, the Supplier ~~SHALL~~shall submit lot samples for testing per the schedule in the ballistic test specification.

Ballistic sample submission process for Anniston purchased material tested at BAE Systems San Jose:

- Supplier ~~SHALL~~shall submit a copy of 091889 Ballistic Test Submittal Form.
- Signed copy of the Ballistic Test form ~~SHALL~~shall be included with the shipping documents for the test sample
- In addition to the marking requirements, specified in the PO and on the drawings, ALL test specimens, shipping containers and associated documents ~~SHALL~~shall be clearly marked "First Article Sample" or "Lot Sample."
- Following Ballistic First Article approval, the Supplier ~~SHALL~~shall submit lot samples for testing per the schedule in the ballistic test specification.

Ballistic sample submission process for Anniston purchased material tested at another testing facility other than BAE Systems San Jose:

- All ballistic test documentation ~~SHALL~~shall be provided.
- The Supplier ~~SHALL~~shall submit lot samples for testing per the schedule in the ballistic test specification.
- The Supplier is responsible for tracking compliance to ballistic testing for each product supplied to BAE Systems CMS.

034 Ballistic Requirements- Metal and Composite Materials

FIRING RECORDS (Plate and Composite):

Formatted: Line spacing: single

The Supplier ~~SHALL~~shall provide a copy of the:

Formatted: Line spacing: single

- Summary ~~Template~~template for ~~Armor Product~~armor product 093550, held on the purchasing website.
 - a. Submission of this form is only required for parts fabricated from the following material specifications:
 - i. Aluminum Armor
 1. MIL-DTL-32262
 2. MIL-DTL-32341
 3. MIL-DTL-32375
 4. MIL-DTL-32505
 5. MIL-DTL-45225
 6. MIL-DTL-46027
 7. MIL-DTL-46063
 8. MIL-DTL-46083
 9. MIL-DTL-46192

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

ii. Steel Armor

- ~~1.10.~~ MIL-A-11356
- ~~2.11.~~ MIL-DTL-12560
- ~~3.12.~~ MIL-DTL-32332
- ~~4.13.~~ MIL-DTL-46100
- ~~5.14.~~ MIL-DTL-46177

iii. Titanium Armor

- 1. MIL-DTL-46077
- ~~2. 19207-12933366~~
- ~~3. 19207-12462708~~

~~b. Any other items listed with CDR034 that do not make use of these listed specifications are not required to complete the submission form 093550.~~

~~e.b.~~ Completion of this form does not exempt the vendor from submission of all other required documentation listed in CDR 034.

- Physical and Chemical Test Reports for armor or allowable non armor options.
 - a. For non-armor options allowed per the print, the Supplier ~~SHALL~~shall submit the physical and chemical test reports for the optional material used. BAE Systems ~~SHALL~~shall be notified of the use of the optional material during documentation submittal.
 - b. Test reports ~~SHALL~~shall be provided in accordance with the applicable material standard and the definitions and requirements therein.
 - c. Certificate is required to state affirmation/compliance to DFARS 252.225-7008 and 252.225-7009.

The Government ~~Ballistic Test Certification~~ballistic test certification, including firing number for each heat/lot of ballistic material.

-All armor material lot and heat certification traceability must be maintained and tracked to the sub-component and or end item the material was consumed in, these records shall cover components and or end items delivered under this purchase order.

- FIRING RECORDS (CASTING):
 - For armor castings and extrusions, the Supplier ~~SHALL~~shall maintain a listing of Government approved firing numbers for all material recipes supplied to BAE Systems.
- FIRING RECORDS (FORGINGS):
 - a. Aluminum armor forgings require a ballistic test for each lot, including longitudinal and transverse tensile tests per MIL-DTL-45225 and the material certificate of analysis.
 - b. Ferrous armor forgings require a ballistic test for each lot, including results for all testing specified in the ballistic test specification and the material certificate of analysis.

MACHINING ALLOWANCES FOR ARMOR PLATE:

In general, mill certifications for armor aluminum and ballistic test certifications are required to be provided at steel, it has been found that machining the surface to reduce thickness designated on a drawing's material note does not affect ballistic properties. If the new machined thickness is tested for ballistics it will meet the requirement of that thickness. This is usually the design thickness. However, mechanical properties depend on the thickness range, generally thinner gages have higher strength than greater thickness, so machining can only be performed within that thickness. For instance, a 2.500 inch 5083 plate cannot be machined to 1.75 inches. In instances where there is no requirement for the thickness of armor material designated in the material note, or a the supplier shall utilize that material thickness to produce the part is machined to final dimensions from. In instances where there is not a thicker section, the required material thickness designated in the material note, the following requirements SHALL apply:

- If the thickness of the armor material is not specified on the material note, thicker Thicker material may be procured and machined to final size with the following limitations:
 - MIL-DTL-46027 alloy 5083 is allowable to machine 25% from within the original thickness to meet requirement applicable ranges specified in the table below.

Min (inch)	Max (inch)
.250	.499
.500	2.000
2.001	3.000
3.001	10.500

- MIL-DTL-32375 (Class 1, All Grades, 7085) – is allowable to machine within the applicable ranges specified in the table below.

Min (inch)	Max (inch)
.500	1.500
1.501	2.000
2.001	3.000

- MIL-DTL-32375 (Class II, 7056) – allowable to machine 10% from the original thickness to meet requirement.

Min (inch)	Max (inch)
1.000	2.000
2.001	3.000

- MIL-DTL-12560 (Class 1) – or 2) – is allowable to machine within the applicable hardness ranges specified in Table 1 in this section, the table below.

- MIL-DTL-12560 (Class 2 & 4) – allowable to machine 25% from original thickness to meet requirement.

Armor Class (MIL-DTL-12560)	Min (inch)	Max (inch)
1	.098	.249
1	.250	.624
1	.625	1.125
1	1.126	1.999
1	2.000	3.999

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Line spacing: single

Formatted: Line spacing: single

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

<u>1</u>	<u>4.000</u>	<u>6.000</u>
<u>2</u>	<u>.098</u>	<u>2.000</u>

Formatted: Font: 10 pt

Formatted: Font: 10 pt

- MIL-DTL-46100 – allowable to machine 25% from original thickness requirement.

Formatted: Font: Calibri

- When the final machined thickness is not called out on the face of the drawing (because it is in the material note) the machined thickness shall be the nominal thickness called out in the material note with a tolerance of +/- .030.

Formatted: Indent: Left: 0.5", Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

- When assessing machining allowances per the above requirements, measurements ~~SHALL~~shall be taken from nominal ordered thickness to the nominal measurement at the thickest section of the component as designated on the drawing.
- Exceptions outside of the allowances in this document must be reviewed and approved by BAE Systems Engineering and requires the submission of a VIR.

~~Note that Class 3 MIL-DTL-12560 armor is not allowable for use in the fabrication of vehicle product and is typically used for other test and evaluation purposes. As a result, machining allowances for this material require submission of a VIR if procured in a thickness other than that requested in the PO.~~

~~Table 1. Machining Allowances for MIL-DTL-12560 Wrought Armor Plate.~~

Armor Class (MIL-DTL-12560)	Allowable Machining Ranges
1	.098 – .249 incl.
	.250 – .624 incl.
	.625 – 1.125 incl.
	1.126 – 1.999 incl.
	2.000 – 3.999 incl.
	4.000 – 6.000 incl.
2	25% original thickness
4	25% original thickness

Formatted: Line spacing: single

MATERIAL REDUCTION OF ARMOR PLATE (STEEL & ALUMINUM):

During the handling and fabrication of armor plates, occasionally small material defects – such as mechanical gouges and scratches – accumulate on the plate surface. In general, surface imperfections that do not affect the functionality of the material or its fitness for fabrication are acceptable and do not need to be repaired. These requirements are outlined in Paragraph 3.11 (MIL-DTL-46027), Paragraph 3.9 & 3.10 (MIL-DTL-32375), and Paragraph 3.2.11 (MIL-DTL-46100 and MIL-DTL-12560).

Given that it is difficult for vendors to assess what surface imperfections may affect the functionality or serviceability of a plate in fabrication, vendors ~~SHALL~~shall assess surface imperfections based on the following criteria:

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

- Identify indications of surface imperfections visually and determine base material type and thickness per applicable engineering drawing.
- Measure plate thickness at the indication site via ultrasound thickness gage, caliper, or other process approved by BAE Systems SQA representatives suitable to accurately measure the indication depth.
 - Ultrasound thickness gage measurements SHALLshall be taken at the deepest area of the surface imperfection. In instances where an indication cannot be assessed in this manner, measurements SHALLshall be taken adjacent to the indication.
 - Measurements by caliper or mechanical measurement SHALLshall be taken at the plate edge nearest the indication. A depth gage SHALLshall then be used to measure the depth of the imperfection at its deepest point and subtracted from the as-measured thickness to determine final thickness in the area of the indication.
 - Imperfections may be deburred in order to allow effective measurement of the indication.
- Compare the measured thickness of the plate to the minimum allowable material thickness per applicable specification. In instances where the thickness at the location of the indication is defined on the drawing, refer to the applicable drawing tolerances for the minimum allowable material thickness.

If material-an imperfection is found to meet or exceed the material specification allowable minimum material thickness at the deepest point of the defect, it is acceptable as-is and no repair is needed. All surface imperfections deemed acceptable by this method SHALLshall be deburred to remove sharp edges. If the material thickness at the deepest point of the imperfection is found to be thinner than the minimum allowable thickness at the deepest point of the defect, the material is non-conforming to thickness per the specification and SHALLit shall be rejected. Tolerances for imperfection depth shall follow material specification allowances based on the plate size used. The Supplier shall have evidence of plate size used in the manufacture of this part supporting tolerance allowances if requested by BAE Systems. Alternatively, vendors with defective indications may submit a VIR to authorize a repair or use as-is.

Table 2. Thickness Tolerances for MIL DTL 46027.

Ordered Thickness (Inches)		Allowable Material Reduction from Specified Thickness (Inches)
Over	Thru	Minus Tolerance
.250	.315	.018
.315	.394	.023
.394	.630	.032
.630	.984	.043
.984	1.575	.055

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

1.575	2.362	.070
2.362	3.000	.100

Table 3. Thickness Tolerances for MIL DTL 32375.

Ordered Thickness (Inches)		Allowable Material Reduction from Specified Thickness (Inches)
Over	Thru	Minus Tolerance
.500	1.000	.043
1.001	1.575	.055
1.576	2.362	.070
2.363	3.000	.100

Table 4. Thickness Tolerances for MIL DTL 12560.

Ordered Thickness (Inches)		Allowable Material Reduction from Specified Thickness (Inches)
Over	Thru	Minus Tolerance
.2500	.3749	.022
.3750	.6249	.025
.6250	.9990	.030
1.0000	1.4990	.035
1.5000	1.9990	.045
2.000	2.9990	.065
3.000	3.9990	.070

Table 5. Thickness Tolerances for MIL DTL 46100.

Ordered Thickness (Inches)	Allowable Material Reduction from Specified Thickness (Inches)
----------------------------	--

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Specified Thickness	Minus Tolerance
.1250-.3125	.019
.313-.750	.023
.751-1.000	.026
1.001-1.1875	.031
1.188-1.4375	.036
1.438-1.5625	.039
1.563-1.750	.043
1.751-2.000	.048

Formatted: Line spacing: single

THERMAL CUTTING OF STEEL ARMOR PLATE:

~~SHALL~~shall meet the following requirements:

- Parts produced by thermal cutting of plate material ~~SHALL~~shall be subject to process qualification. Submission of parts which are thermally cut, ~~SHALL~~shall meet the following requirements:

APPLICABILITY:

- Thermal cutting processes include any methods, which rely on, or result in, the generation of temperatures in excess of 1,300 °F at the point of cutting. These processes include, but are not limited to laser, plasma, and the family of oxy-fuel cutting processes. These processes do not include abrasive cutting methods such as waterjet, abrasive disk or saw, and machining. Products that are first cut by thermal process (such as plasma) and then finished to final dimension by ~~abrasive~~-method (s) (such as machining or grinding) are not subject to the qualification requirements for thermal cutting processes.
- MIL-DTL-46100 materials, all tempers.
- MIL-DTL-12560 materials, Class 1, Class 2, Class 4a, and Class 4b. Qualification for cutting of Class 1, Class 4a, or Class 4b material ~~SHALL~~shall be applicable to cutting of Class 2 material. Class 3 armor is not intended for use in vehicle applications and is exempt from the requirements of this section.
- MIL-DTL-32332 materials, all tempers.
- MIL-A-11356 materials, all tempers.

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Line spacing: single

PROCEDURE:

- The Supplier ~~SHALL~~shall have a written and controlled procedure for cutting steel armor. ~~Documentation of the procedure SHALL be made available to BAE Systems upon request.~~
- Initial Procedure Qualification Test: -The Supplier ~~SHALL~~shall produce a production quality sample in order to verify that the procedure is capable of achieving edge quality in accordance with the applicable material specification. Documentation for this test ~~SHALL~~shall be submitted ~~per 8.12 of the SQAM,~~ to BAE Systems representatives for acceptance ~~is required~~ prior to working on productions parts. The required tests for initial procedure qualification are as follows:
 - Sample coupons ~~SHALL~~shall be cut with the process to be qualified. Coupons may be on a production part, a sample attached to a production lot, or an independent sample ~~of the same material type, grade and heat. Inspector qualification shall comply to in process qualification details below.~~
 - Visual inspection - no indications of cracking along cut plate edges is acceptable.
 - Non-destructive testing (NDT) per ASTM E1417 or ASTM E1444 or equivalent. Acceptance criteria in accordance with the applicable material standard, ~~no cracking is allowed.~~
 - Heat Affected Zone Hardness (HAZ) will be determined by the hardness indentation at the mid-length of the cut edge. Five (5) measurements ~~SHALL~~shall be taken and equally spaced from the cut edge to a distance of 1.2T or .625 inches (whichever is less).
- Procedure Documentation:- Once the Supplier has completed the evaluations outlined by the Initial Procedure Qualification Test, documentation of the test results ~~SHALL~~shall be submitted to BAE Systems for final review and approval. This report ~~SHALL~~shall contain form 089475, ~~located in the BAE Systems Supplier Website~~ and the following information at a minimum:
 - Material documentation:- Includes material standard, temper, heat or lot number, and material thickness tested.
 - Process documentation:- Includes process type (e.g. plasma, laser, oxyfuel), method of cutting (manual or automatic), and environment (e.g. ambient condition, water immersion, controlled non-reactive environment).
 - Major Processing Parameters: Includes the primary processing parameters affecting the quality of the cut edge. Some examples are shown below but should not be considered an exhaustive list:
 - Laser:- Beam source, cutting power, travel speed, primary shielding gas, travel speed, minimum pre-heat & post-heat (if applicable).
 - Plasma:- Electrode type, voltage, primary cutting gas, travel speed, minimum pre-heat & post-heat (if applicable).
 - Oxy-Fuel:- Cutting gas, gas pressure, travel speed, minimum pre-heat & post-heat (if applicable).
 - Secondary Processing: In some cases, Suppliers may elect to use secondary tempering, grinding, or machining processes to ensure the quality of the cut edge and decrease the propensity for cracking. In these cases, Suppliers are not required to submit their secondary processing as part of the qualification for their thermal cutting procedure.
 - Documentation ~~SHALL~~shall be ~~provided with~~maintained on file supporting the results of visual inspection and NDT in accordance with the initial qualification test. ~~Supplemental documentation may~~ Affirmation of NDT evaluations passing shall be attached to support ~~NDT results~~documented on form 089475.

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

- Documentation ~~SHALL~~shall be provided with the results of the ~~initial qualification test.~~ Supplemental documentation may be attached to support the results of NDT and hardness testing.
- Date, printed name and electronic or hard copy signature ~~SHALL~~shall be included to confirm the validity of the test results from the contracted vendor's authorizing authority. In instances where a vendor sub-contracts work to a secondary shop, the authorizing signature ~~SHALL~~shall be provided by the primary vendor. In these cases, the primary vendor will be responsible for maintaining the qualification records and is accountable for products contracted to them but processed by the secondary shop.

PROCEDURE APPROVAL & PERIOD OF QUALIFICATION:

- The Supplier ~~SHALL~~shall have the procedure qualification for Thermal Cutting of Steel Armor Form number 089475 completed and approved by BAE Systems' Materials Engineering prior to shipment of product. This should include all provisions of the procedure documentation listed.
- After final approval, period of qualification ~~SHALL~~shall be indefinite unless there is a process change or reason to believe that the qualified procedure is no longer capable of meeting the edge quality requirements of the applicable material specification.
- Rejection of a submitted Procedure Documentation for qualification, or revocation of an existing qualification, ~~SHALL~~shall be followed by corrective action for requalification by BAE Systems.

EFFECTIVITY OF QUALIFICATION:

- A qualified procedure is applicable to the following ranges. For a given tested material thickness, the process qualification ~~SHALL~~shall be sufficient for the same process used on materials applicable to the qualification test:
 - $.380 < T$
 - $.380 \leq T < .625$
 - $.625 \leq T < 1.000$
 - $T \geq 1.000$
 - Example:- Vendor A qualifies a laser cutting process, using a CO₂ beam source at 4,500 Watts, at 100 IPM on .500 on Class 1 MIL-DTL-46100 material. That qualification is sufficient to cover MIL-DTL-46100 Class 1 materials, to a minimum thickness including .380 and a maximum thickness excluding .625.
- Procedures qualified prior to Rev 09 ~~SHALL~~shall remain in effect under the provisions of this release unless there is reason to believe that the qualified procedure is no longer capable of meeting the edge quality requirements of the applicable material specification.

PROCESS INSPECTION:

- Only qualified inspection personnel ~~SHALL~~shall conduct visual and NDT process inspections. Documentation of personnel's inspection qualification ~~SHALL~~shall be kept and provided to BAE Systems upon request.
 - Inspection personnel ~~SHALL~~shall be certified per the contract specification or a written practice in accordance with ASNT SNT-TC-1A, AWS QC1, CSA W178.2, or comparable.
- Process inspection ~~SHALL~~shall consist of the following regardless of further grinding, machining or providing as thermally cut material:
 - Visual inspection to be performed by qualified personnel, conducted in accordance with the Supplier's procedure. Inspection frequency ~~SHALL~~shall be 100%.
 - NDT will be in accordance with ASTM E1417, ASTM E1444, or equivalent. Frequency ~~SHALL~~shall be General Inspection level II, AQL 2.5%, spec ANSI/ASQ Z1.4. If rejectable indication is found, institute 100% inspection of subject lot.
 - ~~Provided certification SHALL include the inspector's name, credentials, quantity inspected and approved status.~~
 - ~~Evidence of in process inspections shall be maintained and available upon request.~~

DEFINITION:

Lot ~~SHALL~~shall mean "inspection lot" or "inspection batch" of parts of the same material grade, the same thickness and processed continuously under one procedure.

Example – Supplier A cuts 10 Part Numbers, with different quantities, all from the same thickness of high hardness armor. If they are processed (cut) in a constant continuous process, then the collection of parts can be inspected as one lot. Material certifications supporting components within an assembly ~~SHALL~~shall be labeled with the component part number or identifier it correlates to.

036 REACH Assessment

~~Refer~~All parts and materials shall comply with Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) regulation latest revision and evaluated to ~~SQAM section 9.5.3~~the latest published candidate list. The manufacturer or Supplier ~~SHALL submit~~shall provide a REACH ~~assessment with each PO listing the identified substances found on the current SVHC list. A copy of the assessment is to be included~~Declaration with each shipment ~~against the PO, including the date, PO number, and part number. This includes any surface treatments (plating, coating, painting, etc.) performed by sub-tier Suppliers. The Supplier is responsible for flowing down this requirement to their sub-tier Suppliers. If available, the Chemical Abstracts Service (CAS), identification number of the SVHC substance SHALL~~shall be included in the REACH Assessment. If there are no ~~SVHC substances~~Substances of Very High Concern (SVHC) present in the article, the Supplier's REACH Assessment should state "Article supplied does not contain SVHC". ~~The REACH Assessment SHALL include the date of the assessment along with the PO number and the part number.~~

037 CPNA (Critical Part Number Assessment) Assigned Item

~~Items assigned with this CDR are applicable to the BAE CPNA process. The BAE CPNA process assigns a BAE Engineer to the supplier to mutually review the suppliers contract review, manufacturing, inspection and packaging and shipping processes. This partnership is to ensure the supplier and BAE are~~

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Line spacing: single

Formatted: Line spacing: single

Formatted: Indent: Left: 0.5", Line spacing: single

Formatted: Space After: 10 pt, Line spacing: single

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

~~completely aligned to the BAE PO contract requirements, ultimately ensuring there are no rejections or late deliveries affecting the supplier or BAE.~~

~~The SVHC list can be found at this link: <https://echa.europa.eu/candidate-list-table>~~

041 Critical Safety Items (CSI)

The Supplier ~~SHALL~~shall provide documentation for all Critical Safety Items (CSI), or Observable Critical Items (OCI) identified for this item by the TDP. **Sample size for this inspection ~~SHALL~~shall be 100% for the identified characteristic (s).** Actual results, including an authorized signature and date of acceptance, traceable to a specific shipment ~~SHALL~~shall be recorded and provided.

Formatted: Line spacing: single

041A Critical Safety Items (CSI) Heat Treat Supplier

The heat treat Supplier ~~SHALL~~shall conduct 100% testing for Hardness Critical Items (HCI). Hardness testing will occur at designated locations identified on the BAE Systems drawing. Hardness testing will be conducted in accordance with the method defined in the Standard Process Specification (SPS) document specified on the drawing. In the event the location for the hardness testing is not indicated on the BAE System's drawing, the heat treat Supplier may select an appropriate location on the part for testing to be conducted. In the event the BAE Systems drawing does not specify an SPS document for hardness testing, hardness testing is to be conducted per ASTM-E18. The actual results, including an authorized signature and date of acceptance, traceable to a specific shipment ~~SHALL~~shall be recorded.

Formatted: Line spacing: single

~~042 SPC Program~~

~~Statistical methods and procedures used by the Supplier to implement and maintain a documented continuous improvement program may be subject to review by BAE Systems' Quality Assurance. Using Statistical Process Control (SPC) methods, tools, and documentation, the Supplier must monitor key characteristics noted directly on the PO or engineering documents. Copies of the control charts, (including notes and corrective actions for assignable causes) must be delivered with each shipment. Processes yielding a Cpk of less than 1.33 require 100% inspection for key characteristics prior to certification and delivery of the production lot. Documented inspection reports SHALL accompany each shipment. The Supplier is responsible for the flow down of this CDR to their subcontractors.~~

~~The supplier shall implement a Variability Reduction Plan (VRP) / Statistical Process Control (SPC) plan for those key processes or Key Characteristics (KC's) that affect form, fit, function, reliability or service as defined by the TDP or purchase order. The (VRP) / (SPC) plan will be compliant to AS9103 and shall be in place before any deliveries begin. Each control characteristic listed in the plan shall be in statistical control as evidenced by control charts. Minimum Cpk=1.33. For attribute data, at least 99.9% conformance to specification or drawing may identify one or more key characteristics by way of special flag, table or notation. Capability for each control characteristic shall have been calculated. The Supplier will perform 100% inspection of any KC's that are determined to be out of control by the SPC charts. Out of control conditions shall have corrective/preventive actions documented and BAE Systems shall be notified.~~

044 Packaging Instructions for Hardware Kits

All hardware and small components kits ~~SHALL~~shall be packaged, marked, and packed as follows unless other requirements are provided through the Purchasing Agreement.

Formatted: Line spacing: single

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

The contents of this kit ~~SHALL~~shall be packaged, identified, consolidated and packed per the instructions below. The BAE Systems PO and/or Engineering drawing provide the part numbers and quantities required for each kit. Packaging of this kit is to be accomplished through good commercial practices and is intended to provide adequate protection of the kit (s) and the kit components during transit and handling as well as for short-term storage.

• Packaging

Cleanliness – Items ~~SHALL~~shall be free of dirt and other contaminants that would contribute to deterioration of the item.

Preservation – Bare steel surfaces ~~SHALL~~shall provide protection such as preservative coatings. Zinc or cadmium plating are not considered bare and will not require preservative protection. Items made from stainless steel material do not require preservative protection. When rubber items are unit packaged in quantities of more than one, the items ~~SHALL~~shall be dusted with talcum (soapstone).

Unit Package – The unit packaging ~~SHALL~~shall consist of an item of the same part number and the specified quantity per kit. Place the required item quantity in a close-fitting poly bag as to keep package cube to a minimum. Use multiple bags per part when applicable. The minimum bag size ~~SHALL~~shall be 3 x 4 inches; the bag ~~SHALL~~shall be a minimum of 3-MIL thick. The bag ~~SHALL~~shall be heat-sealed in a manner to keep the items contained within the bag. The trapped air volume in the bag ~~SHALL~~shall be kept to a minimum to reduce package cube.

Consolidation – Consolidate the required unit packages for each specified part number into a poly bag, 6-MIL thick, or a snug fitting fiberboard carton (a fiberboard carton is preferred method). If a poly bag is used for consolidation, the weight ~~SHALL~~shall not exceed 10 lb. A packing list will be enclosed in each consolidated package detailing the contents, to include: the kit part number, and the part number, description, and quantity for each component included. The bag and/or carton size used for the specified kit ~~SHALL~~shall be identical throughout the contract.

• Marking

Each package used in this kit, ~~SHALL~~shall identify the contents with the applicable part number, nomenclature, quantity, and kit number. For unit packaging and consolidation packages, see Label Example A. The markings for each pack can be printed on a label or applied directly on to the bag or carton. If a label is used it ~~SHALL~~shall meet the requirements as outlined below, and if a label is used to identify a bag, the label may be heat-sealed in the bag along with the item(s). If the label is placed in the bag, the label identification must be able to be read from the exterior of the package. If a Packing List is enclosed in the package, the package is to be marked with "Packing List Enclosed" and must be in the same area and adjacent to where the kit identification is applied.

Age Control – Shelf-life markings ~~SHALL~~shall be shown as part of the item identification data on unit packs, intermediate containers, exterior containers, and unpacked items. Shelf-life markings ~~SHALL~~shall include the manufactured, cured, assembled, or packed date (apply one date), and the expiration or inspect/test date, as appropriate. This information must appear on the unit package unless it is visible through a clear plastic bag, and on the intermediate and exterior container (only

Formatted: Font: 10 pt

Formatted: Font: 10 pt

when unit pack is exterior container). When two, or more unit packs of identical items are marked with different dates, the earliest date must be shown on the intermediate container. Exterior containers and multi-packs containing age control items ~~SHALL~~shall be marked "CONTAINS SHELF-LIFE ITEMS).

- a. Non-extendable shelf-life items: manufactured (MFD) date, cure date, assembled date, package date (subsistence only) (apply one date, as appropriate), and expiration (EXP) date. For items that contain rubber or synthetic elastomers, the expiration date ~~SHALL~~shall be calculated from the cure date of the rubber/elastomer.
- b. Extendable shelf-life items: manufactured date, cure date, assembled date, package date (subsistence only) (apply one date, as appropriate), and inspect/test (INSP/TEST) date. For items that contain rubber or synthetic elastomers, the inspect/test date ~~SHALL~~shall be calculated from the cure date of the rubber/elastomer.

EXAMPLE 1 (Non-extendable)	EXAMPLE 2 (Extendable)	EXAMPLE 3 (Extendable)
MFD DATE 10/10	ASSEMBLED DATE 10/10	CURE DATE 4Q09
EXP DATE 10/13	INSP/TEST DATE 10/13	INSP/TEST DATE 4Q11

Labels - All labels used ~~SHALL~~shall meet or exceed the following requirements: pressure sensitive, water-resistant, size 2 x 2-1/2 inches (min). The part number, nomenclature, quantity, and kit number ~~SHALL~~shall be in a stacked configuration, font size 12 to 14, black ink on white label, and upper-case letters. Direct printing on the bag is also acceptable.

• **Packing**

Palletize and/or consolidate required kit quantities per contract schedule. Before stretch wrapping or banding, place fiberboard on four sides and top to further protect cartons from damage. The palletized load (s) ~~SHALL~~shall be marked with the appropriate shipping address as specified in the Purchasing Agreement. Apply special handling marking "Do Not Stack".



Example A

Unit Pack Label



Example B

Consolidation Pack Label

Formatted: Line spacing: single

Formatted: Line spacing: single

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

046 ~~QUALIFIED PRODUCT LIST~~Qualified Product List (QPL)

Items furnished on this PO which are applicable to the Government, a customer, and/or BAE Systems Qualified Product List (QPL) must be produced by the manufacturers listed on the current QPL.

Formatted: Line spacing: single

053 ~~Dock To Stock Eligibility~~

~~This part number is not eligible for the dock-to-stock program. All CDRs specified apply including the requirement to provide associated certifications, inspection, and test reports.~~

054 AQL 1.0

This item requires inspection at AQL 1.0 to the C=0 Sampling Plan for all major drawing characteristics. Major drawing characteristics are dimensions with a total tolerance of $\leq .010$ or where the characteristic is identified as a "major" by a drawing note or SQAP/QAP/QAR

Formatted: Line spacing: single

055 100% Inspection

This item requires 100% inspection of all critical drawing characteristics. Critical characteristics are any dimensions with a total tolerance of $\leq .001$ or where the characteristic is identified as a "critical" by a drawing note or SQAP/QAP/QAR.

Formatted: Line spacing: single

056 PPAP-Level 1

The Supplier ~~SHALL~~shall complete a Production Part Approval Process (PPAP) in accordance with Level 1 of the Production Part Approval Process manual and ~~SHALL~~shall submit a warrant and an appearance approval report as required to BAE Systems for approval.

Formatted: Line spacing: single

057 PPAP-Level 2

The Supplier ~~SHALL~~shall complete a PPAP in accordance with Level 2 of the (PPAP) manual and ~~SHALL~~shall submit the following to BAE Systems for approval:

Formatted: Line spacing: single

- Design record
- Engineering change documents (if applicable)
- Dimensional results with ballooned drawing (all characteristics, including drawing notes, numbered)
- Photograph of the part marking
- Material, performance test results
- Qualified laboratory documentation
- Appearance approval report (if applicable)
- Sample product
- Part Submission Warrant (PSW)

All other requirements of the PPAP ~~SHALL~~shall be completed, retained on file, and made available to BAE Systems upon request.

The Supplier ~~SHALL~~shall NOT ship product to BAE Systems prior to receipt of a signed/approved PSW. Product shipped in advance of PPAP approval ~~SHALL~~shall be subject to rejection and may be returned at the Supplier's expense.

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Process or product changes require PPAP resubmission. Notification to BAE Systems prior to changes is essential, as additional audits/reviews may be required prior to resubmission; such changes are to be communicated to your BAE Systems Procurement Representative via the VIR Form (089725). Process or product changes are defined as changes in the processing of the product that could affect its ability to meet design, durability, and reliability requirements, including:

- Use of a process or material other than those which were previously approved.
- Production from new or modified tools (except perishable tools), dies, molds, patterns, etc., including additional or replacement tooling.
- Production following any refurbishment or rearrangement of existing tooling or equipment.
- Production from tooling and equipment transferred from another manufacturing site.
- Change of a Supplier for parts or services (e.g. heat treating, plating, welding).
- Break in production or product produced after tooling has been inactive for 24 months or more.
- Any change in material, including not only raw material but also chemical compounds or processes (i.e. paints, adhesives, sealers, lubricants, plating, heat treat processes, etc.), which become part of the finished product; this includes changing to an engineering approved alternative material or any change in the sequence of operations.
- Upon request of BAE Systems' Purchasing Representative.

058 PPAP-Level 3

The Supplier ~~SHALL~~shall complete a PPAP in accordance with Level 3 of the PPAP manual and ~~SHALL~~shall submit the following to BAE Systems for approval:

Formatted: Line spacing: single

- Design record
- Authorized Engineering change documents (if applicable)
- Customer Engineering approval (if required)
- Design Failure Modes and Effects Analysis (DFMEA)
- Process flow diagrams
- Process Failure Modes and Effects Analysis (PFMEA)
- Control plan
- Measurement system analysis studies
- Dimensional results with ballooned drawing (all characteristics, including drawing notes, numbered)
- Photograph of the part marking
- Records of material/performance test results
- Initial process studies
- Qualified laboratory documentation
- Appearance Approval Report (AAR), if applicable
- Sample production parts
- Master sample
- Checking aids
- Customer specific requirements
- Part Submission Warrant (PSW)

All other requirements of the PPAP ~~SHALL~~shall be completed, retained on file, and made available to BAE Systems upon request.

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

The Supplier ~~SHALL~~shall NOT ship product to BAE Systems prior to receipt of a signed/approved PSW. Product shipped in advance of PPAP approval ~~SHALL~~shall be subject to rejection and may be returned at the Supplier's expense.

Process or product changes require PPAP resubmission. Notification to BAE Systems prior to changes is essential, as additional audits/reviews may be required prior to resubmission; such changes are to be communicated to your BAE Systems Procurement Representative via the VIR form (089725). Process or product changes are defined as changes in the processing of the product that could affect its ability to meet design, durability, and reliability requirements, including:

- Use of a process or material other than those which were previously approved.
- Production from new or modified tools (except perishable tools), dies, molds, patterns, etc., including additional or replacement tooling.
- Production following any refurbishment or rearrangement of existing tooling or equipment.
- Production from tooling and equipment transferred from another manufacturing site.
- Change of a Supplier for parts or services (e.g. heat treating, plating, welding).
- Break in production or product produced after tooling has been inactive for 24 months or more.
- Any change in material, including not only raw material but also chemical compounds or processes (i.e. paints, adhesives, sealers, lubricants, plating, heat treat processes, etc.), which become part of the finished product; this includes changing to an engineering approved alternative material or any change in the sequence of operations.
- Upon request of BAE Systems' Purchasing Representative.

059 PPAP-Level 4-Predefined Requirements

The Supplier ~~SHALL~~shall complete a PPAP in accordance with Level 4 of the PPAP manual and ~~SHALL~~shall submit the following to BAE Systems for approval:

Formatted: Line spacing: single

- Design record
- Authorized Engineering change documents (as applicable for Supplier designed product)
- Customer Engineering approval (if required)
- Process flow diagrams
- Process Failure Modes and Effects Analysis (PFMEA)
- Control plan
- Dimensional results with ballooned drawing (all characteristics, including drawing notes, numbered)
- Photograph of the part marking
- Records of material/performance test results
- Initial process studies (for critical/Safety/Significant Characteristics identified on the drawing)
- Qualified laboratory documentation
- Checking aids (picture of non-standard/special acceptance fixtures, e.g. holding fixture, not applicable to standard inspection equipment, i.e. calipers)
- Customer specific requirements
- Part Submission Warrant (PSW)

All other requirements of the PPAP are waived for this order and do not need to be completed.

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

The Supplier ~~SHALL~~shall not ship product to BAE Systems prior to receipt of a signed/approved PSW. Product shipped in advance of PPAP approval ~~SHALL~~shall be subject to rejection and may be returned at the Supplier's expense.

Process or product changes require PPAP resubmission. Notification to BAE Systems prior to changes is essential, as additional audits/reviews may be required prior to resubmission; such changes are to be communicated to your BAE Systems Procurement Representative via the VIR form (form 089725). Process or product changes are defined as changes in the processing of the product that could affect its ability to meet design, durability, and reliability requirements, including:

- Use of a process or material other than those which were previously approved.
- Production from new or modified tools (except perishable tools), dies, molds, patterns, etc., including additional or replacement tooling.
- Production following any refurbishment or rearrangement of existing tooling or equipment.
- Production from tooling and equipment transferred from another manufacturing site.
- Change of a Supplier for parts or services (e.g., heat treating, plating, welding).
- Break in production or product produced after tooling has been inactive for 24 months or more.
- Any change in material, including not only raw material but also chemical compounds or processes (i.e., paints, adhesives, sealers, lubricants, plating, heat treat processes, etc.), which become part of the finished product. This includes changing to an engineering approved alternative material or any change in the sequence of operations.
- Upon request of BAE Systems' Purchasing Representative.

060 PPAP-Level 4-Unique Requirements

The Supplier ~~SHALL~~shall complete a PPAP in accordance with Level 4 of the PPAP manual and ~~SHALL~~shall submit requirements as specified in the PPAP requirements checklist included as part of the Purchasing Agreement. All other requirements of the PPAP ~~SHALL~~shall be completed, retained on file, and made available to BAE Systems upon request. Inspection data ~~SHALL~~shall be accompanied by a ballooned drawing (all characteristics, including drawing notes, numbered) and a photograph of the part marking.

Formatted: Line spacing: single

The Supplier ~~SHALL~~shall NOT ship product to BAE Systems prior to receipt of a signed/approved PSW. Product shipped in advance of PPAP approval ~~SHALL~~shall be subject to rejection and may be returned at the Supplier's expense.

Process or product changes require PPAP resubmission. Notification to BAE Systems prior to changes is essential, as additional audits/reviews may be required prior to resubmission. Such changes are to be communicated to your BAE Systems Procurement Representative via the VIR Form 089725. Process or product changes are defined as changes in the processing of the product that could affect its ability to meet design, durability, and reliability requirements, including:

- Use of a process or material other than those which were previously approved.
- Production from new or modified tools (except perishable tools), dies, molds, patterns, etc., including additional or replacement tooling.
- Production following any refurbishment or rearrangement of existing tooling or equipment.
- Production from tooling and equipment transferred from another manufacturing site.
- Change of a Supplier for parts or services (e.g. heat treating, plating, welding).
- Break in production or product produced after tooling has been inactive for 24 months or more.

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

- Changes in material, including raw material, chemical compounds or processes (i.e. paints, adhesives, sealers, lubricants, plating, heat treat processes, etc.), which become part of the finished product, including changing to an engineering approved alternative material or any change in the sequence of operations, upon request of BAE Systems' Purchasing Representative.

061 PPAP-Level 5

The Supplier ~~SHALL~~shall complete a PPAP in accordance with Level 5 of the PPAP manual and ~~SHALL~~shall retain all documentation at their facility. Inspection data ~~SHALL~~shall be accompanied by a ballooned drawing (all characteristics, including drawing notes, numbered) and a photograph of the part marking. The documentation ~~SHALL~~shall be made available to BAE Systems upon request.

064 York CAGE Code

The CAGE code to be marked on this part is 06085.

~~065 San Jose CAGE Code~~

~~The CAGE code to be marked on this part is 80212.~~

068 Sterling Heights CAGE Code

The CAGE code to be marked on this part is 6BTJ2

083 Electrostatic Discharge (ESD)

- Supplier ~~SHALL~~shall have an ESD program in place per ANSI/ESD S20.20.
- Supplier ~~SHALL~~shall protect the parts using approved ESD protective packaging per MIL-STD-2073 preservation code GX.
- Labeling ~~SHALL~~shall be per MIL-STD-130 and MIL-STD-129.

084 Process Failure Mode and Effects Analysis (PFMEA) and Control Plans (CP)

A. PFMEA AND CONTROL PLANS PER THE TOP LEVEL DRAWING, AND FLOW DOWN TO ALL SUPPLIERS

- The contractor ~~SHALL~~shall develop and implement the use of PFMEA and CPs that ensure compliance with the requirements of this contract. The PFMEA and CP must involve the entire production system and flow down of these requirements to its Suppliers.
- The contractor ~~SHALL~~shall submit, for BAE Systems approval, an implementation plan, which describes in detail: schedule, milestones, exception criteria, submission methodology and Supplier flow down requirements. Specific processes in the manufacturing of the components must be identified that are used to ensure conformance to the requirements. The implementation plan is to be completed and submitted 30 days following receipt of the contract.
- Control plans ~~SHALL~~shall include outputs from the PFMEA's. Special or key characteristics, whether identified by the Customer or the Supplier, must be used in the development of the control methods. The control methods must also include specific reaction plans when any undesirable measurement results are obtained. The reaction plans, in conjunction with the inspection/test frequency ~~SHALL~~shall effectively mitigate the risk of suspect material being released for shipment from the contractor's/Supplier's facility.

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Line spacing: single

Formatted: Line spacing: single

Formatted: Line spacing: single

Formatted: Font: +Headings (Cambria), 12 pt, Font color: Accent 1, Not All caps

Formatted: Indent: Left: 0.25", Line spacing: single

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

- CPs ~~SHALL~~shall be treated as a living document and ~~SHALL~~shall always reflect the current process. CPs ~~SHALL~~shall be controlled documents and retained for the life of the contract.
- The contractor ~~SHALL~~shall use Automotive Industry Action Group (9AIAG) publications "Potential Failure Mode and Effects Analysis" version 4, 2008, and "Advanced Product Quality Planning and Control Plan" version 2, 2008 for development and use of PFMEAs and CPs.

B. PFMEA AND CONTROL PLANS PER THE TOP LEVEL DRAWING, TIER I & II SUPPLIERS

- The Contractor ~~SHALL~~shall develop and implement the use of PFMEA and CPs that ensure compliance with the requirements of this contract. The PFMEA and CP must involve the entire production ~~system as defined on the top-level drawing.~~
- ~~system as defined on the top-level drawing.~~
- The Contractor ~~SHALL~~shall submit, for BAE Systems approval, an implementation plan, which describes in detail: schedule, milestones, exception criteria, and submission methodology. Specific processes in the manufacture of the components must be identified that are used to ensure conformance to the requirements. The Implementation plan is to be completed and submitted 30 days following receipt of the contract.
- Control plans ~~SHALL~~shall include outputs from the PFMEAs. Special or key characteristics, whether identified by the Customer or the Supplier, must be used in the development of the control methods. The control methods must also include specific reaction plans when any undesirable measurement results are obtained. The reaction plans, in conjunction with the inspection/test frequency ~~SHALL~~shall effectively mitigate the risk of suspect material being released for shipment from the Supplier's facility.
- CPs ~~SHALL~~shall be treated as a living document and ~~SHALL~~shall always reflect the current process. CPs ~~SHALL~~shall be controlled documents and retained for the life of the contract.
- The Contractor ~~SHALL~~shall use Automotive Industry Action Group (9AIAG) publications "Potential Failure Mode and Effects Analysis" version 4, 2008, and "Advanced product Quality Planning and Control Plan" version 2, 2008 for development and use of PFMEAs and CPs.

Formatted: Line spacing: single

085 First Article Inspection

The Contractor ~~SHALL~~conduct First Article Inspection ~~supplier shall complete an~~ (FAI) in accordance with ~~(IAW) the most current latest revision of SAE AS9102 on the entire TDP and contractual requirements for all provided parts and those not previously subjected.~~

~~The supplier shall validate their FAI complies to FAI requirements in accordance with the SQAM, to ensure Supplier product/processes have the capability of meeting design AS9102 standard and/or specification requirements submit to BAE Systems a minimum of 10 days prior to shipment. Shipment of product is not allowed until BAE Systems provides acceptance of the submittal. FAIs SHALL be conducted, reviewed, and submitted a minimum of 5 days prior to shipment. Where changes require only a delta FAI, the delta FAI will be limited to the impact of the change, only. The customer reserves the right to review any or all associated FAI documentation at its discretion.~~

Formatted: Space After: 0 pt, Line spacing: single

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

086 Counterfeit Material Program

Prior to first product delivery, the Supplier is required to submit and gain approval by BAE Systems Procurement, documentation confirming the traceability of parts must be delivered where produced by the Original Equipment/Component Manufacturer or sourced directly from an authorized distributor. Parts

The supplier shall indicate conformance to each drawing note on Form 3. For drawing notes pertaining to part marking, Supplier shall provide supporting photograph(s) as evidence of compliance. FAI package shall include a COC and or packing slip for all Commercial Off The Shelf (COTS) and/or Standard Catalogue Items (SCI). If a drawing note is not applicable, annotate with N/A and a brief comment as to why.

Where a non-conformance is identified through FAI, Supplier is not allowed to ship without BAE Systems written authorization using VIR form 089725. Supplier shall follow below for documenting:

- AS9102 Form 1 Field 19 shall be checked "yes"
- AS9102 Form 1 field 8 and form 3 field 12 shall list the BAE Systems change number Request for change (RFC) or variance number / Request for variance (RFV).
- AS9102 form 3 field 11 record Supplier internal non-compliance number.

086 Counterfeit Electronic Material COC

The Supplier shall submit with each shipment, the chain of custody traceability between original OEM / OCM and authorized franchised distributor that traces value added processing for each electronic part, subpart, component, and/or subcomponent, with traceability of compliance to the original OEM, OCM provider. This includes but is not limited to a CoC, performance / test reports and material certifications. In the event acquisition of product cannot be obtained through the original OEM / OCM or Authorized franchised distributor notification and approval from BAE Systems is required. Supplier shall affirm:

- Items under this purchase order are new, unaltered and original condition compliant to the purchase order.
- The Supplier is an authorized distributor for the specific product line applicable to the OCM / OEM goods.
- The Supplier shall maintain a process compliant with AS5553 at minimum, unless this procurement is subject to DFAR 252.246-7007, in which case the requirements of DFAR 252.246-7007 shall take precedence.
- The Supplier maintains a process to verify goods are not counterfeit which may include but is not limited to GIDEP monitoring, internal or external testing compliant to AS6171.
- Where testing is required to verify authenticity of an item (s) BAE Systems shall be notified and conditions / locations of testing shall be agreed upon prior to conducting testing.

086A Counterfeit Material COC (Non-Electronic)

The Supplier shall submit with each shipment, chain of custody traceability between the Supplier and the original OEM / OCM and any authorized distributor utilized in the procurement of raw materials, components, and/or subcomponents. This includes but is not limited to a CoC, performance / test reports and material certifications.

Supplier shall affirm:

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

- That the Supplier is an authorized distributor for the specific product line applicable to the OCM / OEM goods.
- That raw materials, components, and/or subcomponents under this purchase order are new, unaltered and original condition and compliant.
- Where testing is required to verify authenticity of raw materials, components, and/or subcomponents, BAE Systems shall be notified, and conditions / locations of testing shall be agreed upon prior to conducting testing.
- Raw materials, components, and/or subcomponents from sources other than the OEM/OCM or authorized distributor will require submission and approval, by BAE Systems Procurement, of CoC, certificates of origin and/or performance test reports. ~~With every delivery, the Supplier is required to provide a certificate of authenticity stating compliance with sourcing from OEM/OCM, authorized distributor or a BAE Systems pre-approved Supplier. This requirement is applicable to Phoenix for hardware and electronic purchases and to CMS for electronic purchases only prior to first delivery.~~

087 Material Workmanship Standard

The Supplier ~~SHALL~~shall conduct a visual inspection of product delivered in accordance with and compliant to BAE Systems Inc. 093815 – Supplier Workmanship Standard and/or 093435 – Soft Goods Workmanship Standard. If there are any questions, please submit a VIR for clarification.

Formatted: Line spacing: single

090 Lot Homogeneity

- A. A lot ~~SHALL~~shall be defined as a homogeneous collection of production units. ~~Homogeneity SHALL be~~ A lot is considered to exist, provided a given lot has been homogenous when it is produced by ~~one a single~~ manufacturer, ~~in one unchanged process,~~ using the same ~~controlled manufacturing process,~~ materials and methods, ~~in accordance with the same drawings, same drawing revisions, same specification and specifications, and same specification,~~ revisions. All product units in a lot ~~SHALL~~shall be in accordance with the specification and ~~SHALL~~shall comply with the homogeneity criteria specified herein, ~~regardless of the type of inspection procedure applied to determine conformance with the following requirements:~~
- B. The lot ~~SHALL~~eshall consist of a single production run as defined by the purchasing agreement ~~line item~~Line-Item quantity.
- C. The Supplier ~~SHALL~~shall deliver a ~~Certificate of Conformance (CoC) stating as objective evidence demonstrating lot homogeneity exists to include:~~that includes:
 - Supplier's name and address
 - BAE Systems' Purchasing Agreement number and line number
 - BAE Systems' item number, description, and revision as specified ~~on a~~in the Purchasing Agreement
 - Unique Item Identifier, i.e., date codes, lot codes, heat codes, serializations, unique item identifiers, or batch identifications as applicable.
 - Quantity
 - Signature, printed name, and title of signer (electronic or digital signatures are acceptable)
 - Date

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

091 HVP Lot Sampling Method

- A. Key characteristics, as defined by AFH100604, ~~SHALL~~the symbol (KC) shall be 100% inspected unless Ppk > 1.6. If a key characteristic process is achieving a Ppk > 1.6, as

Formatted: Font: Calibri

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

B. Critical characteristics, as defined by the symbol (C), shall be verified IAW MIL-STD-1916, verification Level VII, unless otherwise noted.

A.C. Major characteristics, as defined by the symbol (M), shall be verified IAW MIL-STD-1916, verification level of process control is maintained-IV, unless otherwise noted.

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

C-E. It is ~~ultimately~~ the Supplier's responsibility, based on their production process, to adopt appropriate verification levels for each characteristic to ensure product compliance, but ~~SHALL~~shall not be less than the assigned ~~minimums~~minimum ~~verification levels specified~~ herein.

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

Formatted: Font: Calibri

092 Ammunition Data Card (ADC)

The Supplier ~~SHALL~~ submit an Ammunition Data Card (ADC) with each delivery utilizing DD-FORM-1650-~~as objective evidence of ammunition lot manufacturing, traceability, inspection, and testing.~~

092A As-Built Configuration List (ABCL)

A. The Supplier ~~SHALL~~shall submit an ~~as-built configuration data~~As-Built Configuration list (ABCL) with each completed part or assembly at the time of shipment: as objective evidence demonstrating the final manufactured configuration, product traceability, and conformity to the approved product configuration.

B. The file name of the ABCL for each part or assembly in a lot ~~SHALL~~shall be identified by part number, revision letter/number, and serial number. The ABCL ~~SHALL~~shall be provided in an electronic ~~media matrix/~~spreadsheet ~~or matrix~~ format, listing all parts and including the following information for the following part in the assembly:

- Indentured Level
- Part Numbernumber
- Part Revisionrevision
- Part Namedname
- Serial / Lot Numberlot number (as applicable)
- Quantity
- As Builtbuilt drawing revision Letter
- Related Engineering Orderengineering order number

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

- Authorized Material Review Board (MRB) dispositions (Ex. VIR, NC, etc.)
- Manufacturer/Supplier
- Date of Manufacture/manufacture

093 Product Risk Management (PRM)

Product Risk Management (PRM) shall be applied to the product, as shown on the Top-Level drawing and extended to sub-tier Suppliers.

The contractor shall develop and implement a PRM, which shall include the use of a Process Flow Diagram (PFD), a Process Failure Mode and Effect Analysis (PFMEA), and a Control Plan (CP) to ensure compliance with the requirements of this contract (Quality and Delivery). The PRM approach shall be applied to the entire production system and shall extend to include sub-tier processes.

The contractor shall submit the PRM package within 30 days following receipt of this contract and shall consist of a completed PFD, PFMEA, and CP.

The Control Plan shall be developed based on the outputs of the PFMEA. It shall address special or key characteristics identified by the Customer or Supplier and shall incorporate these into the control methods. The Control Plan shall also specify reaction plans to be implemented when undesirable measurement results are obtained. These reaction plans, combined with inspection and test frequencies, shall effectively mitigate the risk of suspect material being released for shipment from the contractor's or Supplier's facility.

The PRM package shall be treated as a living document and shall always reflect the current process for the specific product. Any changes to the original process shall require a revised submission of the PRM package.

The Contractor shall reference and follow the BAE Systems' (PRM) guidelines and templates, as outlined in the PRM package found in the Supplier portal (link)

094 Obsolescence DMSMS Monitoring

The Supplier shall provide one of the following:

- OBSOLESCENCE DIMINISHING MANUFACTURING SOURCES & MATERIAL SHORTAGES (DMSMS) HEALTH ANALYSIS

A summary report of the obsolescence health and lifecycle forecast. Supplier may use any formatting but shall include:

- a) Projection of top-level life cycle status in years
- b) List of components at risk of going obsolete within the purchase order PoP
- c) Planned efforts for design updates that would create a change to the current qualified configuration
- d) Quantity of on hand inventory for items affected by Obsolescence/DMSMS

Or

© BAE Systems

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left

Formatted: Font: 10 pt

Formatted: Font: 10 pt

• COMMERCIAL PARTS LIST

A list of the commercial part numbers contained in the item. The list shall not include any BOM structure, Proprietary Information, Quantity, or Internal part numbers. BAE Systems will conduct Obsolescence DMSMS surveillance of the list and provide notification to the supplier to adjudicate when an event occurs. Format shall be Excel and include only the following:

- a) Point of contact to notify of Obsolescence DMSMS event
- b) Commercially available part number
- c) Cage code if applicable for commercially available part number

Formatted: Line spacing: single

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, Italic

Formatted: Normal, Left